

460AUS-NNA1

ASCII to OPC UA

FEATURES

- Parse ASCII/HEX data in up to 50 segments by delimiter or offset
- Concatenate up to 50 data segments into a string
- Fully configurable OPC
 UA server
- Up to 10 read and write groups with up to 200 nodes per group
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect Serial ASCII devices to an OPC UA Client

The 460AUS moves data between a serial ASCII device and up to three OPC UA clients.

Best of all, the product comes with a 5-year warranty.

How Do I Use the 460AUS-NNA1 in My Application?

Incoming and outgoing ASCII data messages are parsed into data segments and given a data type. Those values are then mapped into OPC UA data objects. It's really that simple to convert data to the information systems you need to monitor your application.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

ASCII FEATURES		
Operation Mode	Bidirectional ASCII Transmit and Receive	
Maximum Number of Devices Supported	1	
Concatenation	Concatenate up to 50 segments data in a delimeted ASCII sting	
Maximum Number of ASCII Characters Transferred	1024 in each direction	
Delimiter Processing	Incoming delimiters can be automatically removed; Outgoing delimiters automatically added if configured	
Parsing	Parse string of ASCII data in up to 50 segments by delimiter or offset	
OPCUA SERVER FEATURES		
Operation Mode	OPC UA Server	
Simultaneous Connections Supported	3	
Max number of Input Nodes per Node Type	200	
Max number of Output Nodes per Node Type	200	
Array Support	Boolean,64 Bit Integer, 64 Bit Unsigned Int and 64 bit Float	
Profiles Supported	UA 1.03 Micro Embedded Server and Data Access	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENT	AL	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	DIN Rail Mount
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	. '
ENCLOSURE / HARDWARE		
Size	3.88" x 2.57" x 1.06"	
Weight	5.5 oz	
Enclosure Type	Anodized Aluminum	2.57
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	Note: All dimensions
GATEWAY FEATURES & FUNCTIONS		are in Inches
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	60000 00
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460AUS-NNA1	Connects up to three OPC UA clients up to two ASCII devices









