460BC-N34



Interconnect Up to 32 BACnet/IP Servers

FEATURES

- Fully configurable BACnet/IP client
- BACnet/IP supports device, binary I/O/V, analog I/O/V, multistate I/O/V, and character string value object types
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- 5-Year Hardware Warranty

Connect Up to 32 BACnet/IP Servers

The 460BC can move data between up to 32 BACnet/IP servers on your network. Best of all, the product is made in the USA, always in stock, and comes with a five-year warranty.


How Do I Use the 460BC-N34 in My Application?

Use data manipulation to modify your data as you transfer it between devices. The manipulation fields allow up to three operations. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

BACnet/IP Client FEATURES			
Operation Mode	BACnet/IP Client		
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value		
Supported Service Codes Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A Dynamic Binding-A			
Maximum Connections	32		
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes		
Scan Line Support	Up to 128 Objects		

ELECTRICAL / ENVIRONMENT	AL		
DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA		
Maximum Baud Rate	115K baud	LEOS	
Operating Temperature	-40 C to 85 C		h
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	i po	
ENCLOSURE / HARDWARE			
Size	4.2" x 3.25" x 1"	3.25	
Weight	7 oz		
Enclosure Type	Anodized Aluminum	9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	
Mounting	Din rail or panel mount		
LEDs	Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side	1.00 4.19 1.00	Ţ
INCLUDED WITH GATEWAY	, ,		
3' Power Cable with Flying lead	s Manual	Panel Mount	
Complete, Unlimited Access to Industry Leading Support Staff.	our 5 Year Hardware Warranty		
CATALOG #	DESCRIPTION	INE YEAR	3
460BCkN34	Connect up to 32 BACnet/IP servers	*5*	
CAT5 Cross over cable for direction to PC during programming	ct	NOT EXACTLY WHAT YOU I Real Time Automation offers a fu Give us a call at 1-800-249-1612 www.rtautomation.com/prc customizations for unique applications.	F

ELECTRICAL / ENVIRONMENTAL