460BCDHM-D2E

BACnet/IP Servers to Legacy DH+ PLCs

FEATURES

- Fully configurable BACnet/IP client
- BACnet/IP supports device, binary I/O/V, analog I/O/V, multistate I/O/V, and character string value object types
- Fully configurable DH+ device
- Connects up to as many as 32 DH+ devices
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Control up to 32 BACnet/IP Server Devices from a Serial PLC5 or SLC PLC

You can now control a network of 32 BACnet/IP server devices from a legacy Allen-Bradley serial PLC. It's the perfect tool to save legacy PLCs from the scrap pile. You can now extend the function of the legacy PLCs you already have.

How Do I Use the 460BCDHM-D2E in My Application?

For most applications, the mapping is very straightforward. PLC data table values like N7:200 and F9:1 are mapped directly to BACnet analog and binary values. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

BACNET IP CLIENT FEATURES			
Operation Mode	BACnet/IP Client		
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value		
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A		
Maximum Connections	32		
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes		
Scan Line Support	Up to 128 Objects		
DH+ MASTER FEATURES			
Operation Mode	DH+ Master		
PLCs Supported	5/04, PLC5		
Maximum number of Devices supported	32		
Data Type Supported	100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line		
Scan Lines	100 input / 100 output		
Physical Connections	DH+		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
	Recommended (not supplied): Belden 9463 Blue Hose®, 1 Pr #20 Str TC https://www.belden.com/		

ELECTRICAL / ENVIRONMENTAL			
DC Input Voltage	12-24 VDC	3.83	
Maximum Baud Rate	921.6K baud		
Operating Temperature	-40 C to 85 C	O O O	
Certification	CE Approvals	01	
ENCLOSURE / HARDWARE			
Size	5.40" x 3.83" x 1.19"		
Weight	7.6 oz		
Enclosure Type	Anodized Aluminum		
Mounting	Din rail or panel mount		
LEDs	Power LED, DH+ Status LED & general purpose LEDs on side	6.4	
GATEWAY FEATURES & FUNCTIONS			
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.		
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.		
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.		
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway product. Give us a call at 1-800-249-1612. Or, check out a listing a www.rtautomation.com/products. We also offer customizations for unique applications.		
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.		

CATALOG #	DESCRIPTION
460BCDHM-D2E	Connects up to 32 BACnet/IP servers with as many as 32 DH+ devices













MADE IN THE USA

EXPERT SUPPORT

EMPLOYEE OWNED