### 460BMPBS-N70PB

### **PROFIBUS to BACnet MS/TP Subordinates**

## **FEATURES**

- Fully configurable BACnet MS/TP Manager
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Fully configurable PROFIBUS slave
- Supports 244 bytes of data in each direction on PROFIBUS DP
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

## Connect a BACnet MS/TP Device to a PROFIBUS DP Controller

The 460BMPBS moves data between your BACnet MS/TP Subordinate device and your PROFINET controller.

Bridge your factory automation systems with your building automation systems.

#### How Do I Use the 460BMPBS-N70PB in My Application?

BACnet MS/TP data will be mapped into 10 PROFIBUS DP slots. The slot can consist of up to 244 bytes of data from your BACnet MS/TP device.

When writing from your PROFIBUS controller to your BACnet MS/TP device, there will be up to 10 slots each defined by the same types. Data in those slots can be mapped to your BACnet MS/TP device.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

# **Specification**

BACNET MS/TP MANAGER FEATURES		
Operation Mode	BACnet MS/TP Manager Initiator	
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value	
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A	
Maximum Connections	32	
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 128 Objects	
PROFIBUS SLAVE FEATURES		
Maximum Number of Slots	10 Slots in, 10 Slots out	
Slot Data Segment Sizes	2, 4, 8, 16, 24, 32 Bytes	
Each Slot Can be Defined for a Single Data Type of	Int8, int16, int32, int64, UInt8, Uint16, Uint32, Uint64, float, double, binary8, binary16 or binary32, Short String	
Total Data Supported	244 Bytes in each direction	
Maximum Profibus DP Controller Connections	1	
Baud Rates Supported	Autobaud (9600, 19.2K, 45.45K, 93.75K, 187.5K,500K, 1.5M, 3M, 6M, 12M bits per second)	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENT		
DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA	
Maximum Baud Rate	115K baud	4.4 1.15
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	
ENCLOSURE / HARDWARE		
Size	4.4" x 3.87" x 1.15"	
Weight	8.5 oz	88 3.87
Enclosure Type	Anodized Aluminum	○ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
Mounting	Din rail or panel mount	
LEDs	Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side	
<b>GATEWAY FEATURES &amp; FUNC</b>	CTIONS	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Panel Mount
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	• •••
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR?  Real Time Automation offers a full line of gateway product: Give us a call at 1-800-249-1612. Or, check out a listing a  www.rtautomation.com/products. We also offer  customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460BMPBS-N70PB	Connects up to 32 BACnet MS/TP Subordinates with a PROFIBUS DP controller









