## 460BMSA-N700

### **BACnet MS/TP Controller to ASCII**

## **FEATURES**

- Fully configurable BACnet MS/TP Subordinate
- BACnet MS/TP supports device, binary I/O, analog I/O, and character string value object types
- Parse ASCII/HEX data in up to 50 segments by delimiter or offset
- Concatenate up to 50 data segments into a string
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

# Deliver Data from your BACnet MS/TP Manager to an ASCII-Based System or Controller

The 460BMSA moves data between a BACnet MS/TP Manager device and serial ASCII.

It's a great tool to implement BACnet MS/TP devices into your PC or embedded applications that support raw ASCII data.

#### How Do I Use the 460BMSA-N700 in My Application?

Up to 1280 BACnet/IP objects can be mapped to and from your BACnet/IP server devices. The data segments can be converted to ASCII. Incoming ASCII string data can be parsed and each segment can be directed BACnet objects.

Need to scale your data or manipulate it with other math functions? The 460BMSA allows you to add scaling to any data, apply simple math operations, add alarming, and control the request speeds of your Manager device.

### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

## **Specification**

BACNET MS/TP RESPONDER FEATURES	
Operation Mode	BACnet MS/TP Manager Responder
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B
Maximum Connections	1
Analog Objects Supported	1200 Input and 1200 Output
Binary Objects Supported	1600 Input and 1600 Output
ASCII FEATURES	
Operation Mode	Bidirectional ASCII Transmit and Receive
Maximum Number of Devices Supported	2
Concatenation	Concatenate up to 50 segments data in a delimeted ASCII sting
Maximum Number of ASCII Characters Transferred	1024 in each direction
Delimiter Processing	Incoming delimiters can be automatically removed; Outgoing delimiters automatically added if configured
Parsing	Parse string of ASCII data in up to 50 segments by delimiter or offset
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
	-40 C to 85 C	
Operating Temperature		Ithernet
Certification	RoHS-Compliant, UL, CUL, CE Approvals	Ithernet 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
ENCLOSURE / HARDWARE	4.40   0.05   4	3.25
Size	4.19" x 3.25" x 1"	1.6
Weight	6.5 oz	Note: Al dimension
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	are nixones
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	-1.00
<b>GATEWAY FEATURES &amp; FUNCTI</b>	ONS	Din Rail
	Set <, <=, >, >=, ==, !=, and change-of-state rules on	Uin Rail
Alarming	any data moving through the gateway. If alarm rule	
0	is triggered an email notification can be sent.	Decel Money
	You can configure up to 9 different users access to	Panel Mount
Gateway Security	diagnostic and configuration screens.	
	Allows for data manipulation during protocol	
Translation Table	translation. Scaling and other data format changes	
Translation rable	can occur in the gateway.	
	Protocol specific status, counters, and error	NOT EXACTLY WHAT YOU WERE LOOKING FOR?
	• • • • • • • • • • • • • • • • • • • •	Real Time Automation offers a full line of gateway products.
Status and Counters	messages are accessible within the gateway's	Give us a call at 1-800-249-1612. Or, check out a listing at
	diagnostics page. They can also be delivered to a	www.rtautomation.com/products. We also offer
	connected device.	customizations for unique applications.
D: 1: 1 : D	Allows users to see and log start up sequences,	
Diagnostic Logging Page	protocol specific messages & error messages.	
	, , ,	

CATALOG #	DESCRIPTION
460BMSA-N700	Connects a BACnet MS/TP Manager with a single ASCII device









