### 460BMSPBS-NNPB

### **PROFIBUS to BACnet MS/TP Manager**

## **FEATURES**

- Fully configurable BACnet MS/TP Subordinate
- BACnet MS/TP supports device, binary I/O, analog I/O, and character string value object types
- Fully configurable PROFIBUS slave
- Supports 244 bytes of data in each direction on PROFIBUS DP
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

## Connect a BACnet MS/TP Manager Device to a PROFIBUS Controller

The 460BMSPBS moves data between a BACnet MS/TP Manager and a PROFIBUS DP controller. It's the perfect tool to tie in all the BACnet MS/TP devices in your automation system to PROFIBUS.

Bridge your factory automation systems with your building automation systems.

#### How Do I Use the 460BMSPBS-NNPB in My Application?

BACnet MS/TP data will be mapped into 10 PROFIBUS DP slots. The Slot can consist of up to 244 bytes of data from your BACnet MS/TP Manager device. When writing from your PROFIBUS controller to your BACnet MS/TP Manager, there will be up to 10 slots each defined by the same types. Data in those slots can be mapped to your BACnet MS/TP Manager device.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

# **Specification**

BACNET MS/TP RESPONDER FEATURES			
Operation Mode	BACnet MS/TP Manager Responder		
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value		
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B		
Maximum Connections	1		
Analog Objects Supported	1200 Input and 1200 Output		
Binary Objects Supported	1600 Input and 1600 Output		
PROFIBUS SLAVE FEATURES			
Maximum Number of Slots	10 Slots in, 10 Slots out		
Slot Data Segment Sizes	2, 4, 8, 16, 24, 32 Bytes		
Each Slot Can be Defined for a Single Data Type of	Int8, int16, int32, int64, UInt8, Uint16, Uint32, Uint64, float, double, binary8, binary16 or binary32, Short String		
Total Data Supported	244 Bytes in each direction		
Maximum Profibus DP Controller Connections	1		
Baud Rates Supported	Autobaud (9600, 19.2K, 45.45K, 93.75K, 187.5K,500K, 1.5M, 3M, 6M, 12M bits per second)		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
Manual			

ELECTRICAL / ENVIRONMENTA	<b>L</b>	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	3.83
Operating Temperature	-40 C to 85 C	
Certification	CE Approvals	, O PHR
ENCLOSURE / HARDWARE		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Size	5.40" x 3.83" x 1.19"	
Weight	7.6 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	4 <u>a</u>
GATEWAY FEATURES & FUNCTIONS		9.5.
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on	
	any data moving through the gateway. If alarm rule	세
	is triggered an email notification can be sent.	
Gateway Security	You can configure up to 9 different users access to	
	diagnostic and configuration screens.	
	Allows for data manipulation during protocol	
Translation Table	translation. Scaling and other data format changes	
	can occur in the gateway.	
	Protocol specific status, counters, and error	NOT EXACTLY WHAT YOU WERE LOOKING FOR?
Status and Counters	messages are accessible within the gateway's	Real Time Automation offers a full line of gateway products.
	diagnostics page. They can also be delivered to a	Give us a call at 1-800-249-1612. Or, check out a listing at
	connected device.	www.rtautomation.com/products. We also offer
	connected device.	customizations for unique applications.
	A11	
Diagnostic Logging Page	Allows users to see and log start up sequences,	
5 65 6 6	protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460BMSPBS-NNPB	Connects a BACnet MS/TP Manager with a PROFIBUS DP controller









