460BSDHM-D2E

Get Your Legacy DH+ PLCs Integrated into Your BACnet/IP Systems

FEATURES

- Fully configurable BACnet/IP server
- BACnet/IP supports device, binary I/O, analog I/O, and character string value object types
- Fully configurable DH+ device
- Connects up to as many as 32 DH+ devices
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Map Your Legacy PLC Data Tables into a BACnet/IP Client

You can now make your legacy serial PLCs look like a BACnet/IP devices! Any of your old serial PLCs like the PLC5 or SLC can now provide data to a BACnet/IP client.

It's the perfect tool to keep those old legacy PLCs from the scrap pile.

How Do I Use the 460BSDHM-D2E in My Application?

For most applications, the mapping is very straightforward. PLC data table values like N7:200 and F9:1 are mapped directly into analog and binary objects in BACnet. The data transfer is bidirectional.

No message instructions and no ladder to alter in many cases.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

BACNET IP SERVER FEATURES		
Operation Mode	BACnet/IP Server	
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value	
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B	
Maximum COV Subscriptions	2800	
Analog Objects Supported	1200 Input and 1200 Output	
Binary Objects Supported	1600 Input and 1600 Output	
DH+ MASTER FEATURES		
Operation Mode	DH+ Master	
PLCs Supported	5/04, PLC5	
Maximum number of Devices supported	32	
Data Type Supported	100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line	
Scan Lines	100 input / 100 output	
Physical Connections	DH+	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
	Recommended (not supplied): Belden 9463 Blue Hose®, 1 Pr #20 Str TC https://www.belden.com/	

ELECTRICAL / ENVIRONMENTAL			
DC Input Voltage	12-24 VDC	3.83	.19 —-
Maximum Baud Rate	921.6K baud		
Operating Temperature	-40 C to 85 C		PWR
Certification	CE Approvals		
ENCLOSURE / HARDWARE		L I ñ	- I
Size	5.40" x 3.83" x 1.19"	TI PU	0
Weight	7.6 oz		= ==1
Enclosure Type	Anodized Aluminum		
Mounting	Din rail or panel mount		
LEDs	Power LED, DH+ Status LED & general purpose LEDs on side	5.4	
GATEWAY FEATURES & FUNCTIONS			il r
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.		
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.		
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.		
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.	
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.		

CATALOG #	DESCRIPTION
460BSDHM-D2E	Connects a BACnet/IP client with as many as 32 DH+ devices









