

Connect Siemens S7 PLCs to DF1 PLCs

FEATURES

- Support for PLC5, SLC and MicroLogix PLCs
- Connect up to 32 DF1 serial devices
- Supports connections to five Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Map Your Legacy PLC Data Tables into Your Siemens S7 PLCs

You can now map your legacy serial PLCs data tables over to your Siemens S7 PLCs! Any of your old serial PLCs like the PLC5, SLC, or MicroLogix can now provide data to S7 PLCs. Connect to your Siemens S7 PLCs. It's the perfect tool to keep those old legacy PLCs from the scrap pile.

How Do I Use the 460DFMSC-N34 in My Application?

For most applications, the mapping is very straightforward. PLC data table values like N7:200 and F9:1 are mapped directly into your Q and I addresses in your Siemens S7 PLCs.

No message instructions and no ladder to alter in many cases.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.


When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: **To move your data where you need it, when you need it, and how you need it.**

| DF1 Master FEATURES | |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------|
| Operation Mode | DF1 Master Full Duplex and DF1 Master Half Duplex |
| PLCs Supported | MicroLogix 1000, SLC 5/03 5/04 5/05, most PLC5s |
| Maximum number of Devices supported | 1 in Full Duplex Mode, 32 in Half Duplex |
| Data Type Supported | 100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line |
| Scan Lines | 100 input / 100 output |
| Physical Connections | RS-485 and RS-232 |
| S7 Client FEATURES | |
| PLC Support | S7 300/400/1200/1500 |
| Maximum Number of PLCs Supported | 5 |
| Maximum Number of Inputs/Outputs per PLC | 150 |
| Maximum Number of Bytes per Scan Line | 400 |
| Memory Area Access | Input (I), Output (Q), and Data Block(DB) |
| Supported Data Types | 8 Bit Int, 16 Bit Int, 32 Bit Int, 32 Bit Float, Bool and Char Array |
| INCLUDED WITH GATEWAY | |
| 3' power cable with flying leads | 5-year hardware warranty |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff |
| Optional: Generic 1761-CBL-PM02 Cable | Optional: NULL Modem Cable |

| ELECTRICAL / ENVIRONMENTAL | |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DC Input Voltage | 8 VDC @ 230mA to 28 VDC @ 80 mA |
| Maximum Baud Rate | 115K baud |
| Operating Temperature | -40 C to 85 C |
| Certification | RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2 |
| ENCLOSURE / HARDWARE | |
| Size | 4.2" x 3.25" x 1" |
| Weight | 7 oz |
| Enclosure Type | Anodized Aluminum |
| Mounting | Din rail or panel mount |
| LEDs | Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side |
| GATEWAY FEATURES & FUNCTIONS | |
| Alarming | Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. |
| Gateway Security | You can configure up to 9 different users access to diagnostic and configuration screens. |
| Translation Table | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. |
| Status and Counters | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. |
| Diagnostic Logging Page | Allows users to see and log start up sequences, protocol specific messages & error messages. |



NOT EXACTLY WHAT YOU WERE LOOKING FOR?
 Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.

| CATALOG # | DESCRIPTION |
|--------------|-------------------------------------------------------------|
| 460DFMSC-N34 | Connect up to five Siemens S7 PLCs with up to 32 DF1 slaves |



MADE IN THE U.S.A.



ALWAYS IN STOCK



READY TO SHIP



EXPERT SUPPORT

