460ECBMS-N34

EtherNet/IP to BACnet MS/TP Manager

FEATURES

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Fully configurable BACnet MS/TP Subordinate
- BACnet MS/TP supports device, binary I/O, analog I/O, and character string value object types
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect EtherNet/IP Adapter Devices to a BACnet MS/TP Manager

The 460ECBMS moves data between a BACnet MS/TP Manager device and an EtherNet/IP network of up to 32 adapter devices. It's the perfect tool to tie in all of your EtherNet/IP devices into your BACnet MS/TP building automation system. Bridge your factory automation systems with your building automation systems.

How Do I Use the 460ECBMS-N34 in My Application?

Up to 496 of data from your EtherNet/IP adapters will be mapped into your BACnet MS/TP Manager. When writing from BACnet MS/TP to EtherNet/IP adapters, up to 496 bytes of BACnet MS/TP data will be mapped to up to 32 EtherNet/IP adapters as EtherNet/IP data.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

Operation Mode	Class 1 I/O Scanner	
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported	
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double	
Maximum EtherNet/IP Adapter Devices	32	
Max Data Per Adapter Connection	Up to 496 bytes in each direction	
Maximum IO Scan Rate	50 msec	
BACNET MS/TP RESPONDER FEATURES		
Operation Mode	BACnet MS/TP Manager Responder	
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value	
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B	
Maximum Connections	1	
Analog Objects Supported	1200 Input and 1200 Output	
Binary Objects Supported	1600 Input and 1600 Output	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENTAL			
DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA		
Maximum Baud Rate	115K baud	LEOS	
Operating Temperature	-40 C to 85 C		
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2		Ped
ENCLOSURE / HARDWARE		3,25	
Size	4.2" x 3.25" x 1"	3.25	
Weight	7 oz		9 8
Enclosure Type	Anodized Aluminum		Per 0
Mounting	Din rail or panel mount		
LEDs	Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side	1.00 4.19	1.00
GATEWAY FEATURES & FUNCTIONS		Din Rail	-
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Panel Mount	- =
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	••••	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.		
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications.	
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.		

CATALOG #	DESCRIPTION
460ECBMS-N34	Connects up to 32 EtherNet/IP adapters with a BACnet MS/TP Manager









