

EtherNet/IP to BACnet MS/TP Master

FEATURES

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Fully configurable BACnet MS/TP responder
- BACnet MS/TP supports device, binary I/O, analog I/O, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Connect EtherNet/IP Adapter Devices to a BACnet MS/TP Master

The 460ECBMS moves data between a BACnet MS/TP master device and an EtherNet/IP network of up to 32 adapter devices. It's the perfect tool to tie in all of your EtherNet/IP devices into your BACnet MS/TP building automation system. Connect to your EtherNet/IP adapters over Wi-Fi using Wi-Fi IEEE 802.11 b/g/n at 2.4GHz with AES encryption 128-bit.

Bridge your factory automation systems with your building automation systems.

How Do I Use the 460ECBMS-NNA1 in My Application?

Up to 496 of data from your EtherNet/IP adapters will be mapped into your BACnet MS/TP master. When writing from BACnet MS/TP to EtherNet/IP adapters, up to 496 bytes of BACnet MS/TP data will be mapped to up to 32 EtherNet/IP adapters as EtherNet/IP data.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.


When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: **To move your data where you need it, when you need it, and how you need it.**

| EtherNet/IP Scanner | |
|---|---|
| Operation Mode | Class 1 I/O Scanner |
| Message Support | Implicit Class 1 Cyclic I/O, Explicit not supported |
| Data Types | BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double |
| Maximum EtherNet/IP Adapter Devices | 32 |
| Max Data Per Adapter Connection | Up to 496 bytes in each direction |
| Maximum IO Scan Rate | 20 msec |
| BACnet MS/TP Slave | |
| Operation Mode | BACnet MS/TP Master Responder |
| Supported Object Types | Device, Binary I/O, Analog I/O, Character String Value |
| Supported Service Codes | Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B |
| Maximum Connections | 1 |
| Analog Objects Supported | 1200 Input and 1200 Output |
| Binary Objects Supported | 1600 Input and 1600 Output |
| INCLUDED WITH GATEWAY | |
| 3' power cable with flying leads | 5-year hardware warranty |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff |
| Manual | |

| ELECTRICAL / ENVIRONMENTAL | |
|---|--|
| DC Input Voltage | 12-24 VDC |
| Maximum Baud Rate | 115K baud |
| Operating Temperature | -40 C to 85 C |
| Certification | RoHS-Compliant, UL, CUL, CE Approvals |
| ENCLOSURE / HARDWARE | |
| Size | 3.88" x 2.57" x 1.06" |
| Weight | 5.5 oz |
| Enclosure Type | Anodized Aluminum |
| Mounting | Din rail or panel mount |
| LEDs | Power LED & 2 general purpose LEDs on side |
| GATEWAY FEATURES & FUNCTIONS | |
| Alarming | Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. |
| Gateway Security | You can configure up to 9 different users access to diagnostic and configuration screens. |
| Translation Table | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. |
| Status and Counters | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. |
| Diagnostic Logging Page | Allows users to see and log start up sequences, protocol specific messages & error messages. |



NOT EXACTLY WHAT YOU WERE LOOKING FOR?
 Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.

| CATALOG # | DESCRIPTION |
|---------------|---|
| 460ECBMS-NNA1 | Connects up to 32 EtherNet/IP adapters with a BACnet MS/TP master |



Made in the
U.S.A.

Always In
Stock

Ready to
Ship

Expert
Support