

CONTACT US! 1-800-249-1612 rtautomation.com

## 460ECDFM-N34

### Connect EtherNet/IP Adapter Devices to a Legacy Serial DF1 PLC

## **FEATURES**

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Support for PLC5, SLC and MicroLogix PLCs
- Connect up to 32 DF1 serial devices
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

# Connect EtherNet/IP devices to your Legacy PLC Data Tables

You can now make your legacy serial PLCs talk to EtherNet/IP adapter devices! Any of your old serial PLCs like the PLC5, SLC, or MicroLogix can now read and write cyclic data from EtherNet/IP devices.

It's the perfect tool to keep those old legacy PLCs from the scrap pile.

### How Do I Use the 460ECDFM-N34 in My Application?

For most applications, the mapping is very straightforward. PLC data table values (File like N7:200 and F9:1) are mapped directly into the input and output assemblies of the mating EtherNet/IP device connections. It really is that simple.

### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

## **Specification**

ETHERNET/IP SCANNER FEATURES	
Operation Mode	Class 1 I/O Scanner
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double
Maximum EtherNet/IP Adapter Devices	32
Max Data Per Adapter Connection	Up to 496 bytes in each direction
Maximum IO Scan Rate	50 msec
DF1 MASTER FEATURES	
Operation Mode	DF1 Master Full Duplex and DF1 Master Half Duplex
PLCs Supported	MicroLogix 1000, SLC 5/03 5/04 5/05, most PLC5s
Maximum number of Devices supported	1 in Full Duplex Mode, 32 in Half Duplex
Data Type Supported	100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line
Scan Lines	100 input / 100 output
Physical Connections	RS-485 and RS-232
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Optional: Generic 1761-CBL-PM02 Cable	Optional: NULL Modem Cable

DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA			
Maximum Baud Rate	115K baud		Os I	
Operating Temperature	-40 C to 85 C	( )		
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	5		Pent
ENCLOSURE / HARDWARE		3.25 0		
Size 4.2" x 3.25" x 1"		3.25		
Weight	7 oz			≥ 0000 00000000000000000000000000000000
Enclosure Type	Anodized Aluminum			Pert 0 0000000
Mounting	Din rail or panel mount			
LEDs	Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side	1.00	4.19	1.00
GATEWAY FEATURES & FUNCI	<b>FIONS</b>	Din Rail		
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Panel Mount		=
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.			
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.			
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.		offers a full line	of gateway products check out a listing at . We also offer
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.			

CATALOG #	DESCRIPTION			
460ECDFM-N34	Connects up to 32 DeviceNet slaves	Connects up to 32 EtherNet/IP adapters with as many as 32 DeviceNet slaves		
		C	WARRANTY	
<u> </u>	6-0-		The second secon	

**ALWAYS IN STOCK READY TO SHIP**  ENGINERD SUPPORT

**5-YEAR WARRANTY** 



solutions@rtautomation.com