

CONTACT US! 1-800-249-1612 rtautomation.com

460ECDFM-NNA1

Connect EtherNet/IP Adapter Devices to a Legacy Serial DF1 PLC

FEATURES

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Support for PLC5, SLC and MicroLogix PLCs
- Connect up to 32 DF1 serial devices
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect EtherNet/IP devices to Your Legacy PLC Data Tables

You can now make your legacy serial PLCs talk to EtherNet/IP adapter devices! Any of your old serial PLCs like the PLC5, SLC, or MicroLogix can now read and write cyclic data from EtherNet/IP devices.

It's the perfect tool to keep those old legacy PLCs from the scrap pile.

How Do I Use the 460ECDFM-NNA1 in My Application?

For most applications, the mapping is very straightforward. PLC data table values (File like N7:200 and F9:1) are mapped directly into the input and output assemblies of the mating EtherNet/IP device connections. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

ETHERNET/IP SCANNER FEATURES		
Operation Mode	Class 1 I/O Scanner	
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported	
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double	
Maximum EtherNet/IP Adapter Devices	32	
Max Data Per Adapter Connection	Up to 496 bytes in each direction	
Maximum IO Scan Rate	50 msec	
DF1 MASTER FEATURES		
Operation Mode	DF1 Master Full Duplex and DF1 Master Half Duplex	
PLCs Supported	MicroLogix 1000, SLC 5/03 5/04 5/05, most PLC5s	
Maximum number of Devices supported	1 in Full Duplex Mode, 32 in Half Duplex	
Data Type Supported	100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line	
Scan Lines	100 input / 100 output	
Physical Connections	RS-485 and RS-232	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Optional: Generic 1761-CBL-PM02 Cable	Optional: NULL Modem Cable	

ELECTRICAL / ENVIRONMENTAL

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	DIN Rail Mount
Operating Temperature	-40 C to 85 C	3.88
Certification	RoHS-Compliant, UL, CUL, CE Approvals	,
ENCLOSURE / HARDWARE		
Size	3.88" x 2.57" x 1.06"	
Weight	5.5 oz	
Enclosure Type	Anodized Aluminum	2.57
Mounting	Din rail or panel mount	
Ds Power LED & 2 general purpose LEDs on side		Note: All dimensions
GATEWAY FEATURES & FUNCTIONS		are in Inches
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

