

CONTACT US! 1-800-249-1612 rtautomation.com

460ECDHM-D2E

Connect EtherNet/IP Adapter Devices to a Legacy Serial DH+ PLC

FEATURES

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Fully configurable DH+ device
- Connects up to as many as 32 DH+ devices
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect EtherNet/IP Devices to Your Legacy PLC Data Tables

You can now make your legacy serial PLCs talk to EtherNet/IP adapter devices! Any of your old serial PLCs like the PLC5 or SLC can now read and write cyclic data from EtherNet/IP devices.

It's the perfect tool to keep those old legacy PLCs from the scrap pile.

How Do I Use the 460ECDHM-D2E in My Application?

For most applications, the mapping is very straightforward. PLC data table values (File like N7:200 and F9:1) are mapped directly into the input and output assemblies of the mating EtherNet/IP device connections. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

ETHERNET/IP SCANNER FEATURES	
Operation Mode	Class 1 I/O Scanner
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double
Maximum EtherNet/IP Adapter Devices	32
Max Data Per Adapter Connection	Up to 496 bytes in each direction
Maximum IO Scan Rate	50 msec
DH+ MASTER FEATURES	
Operation Mode	DH+ Master
PLCs Supported	5/04, PLC5
Maximum number of Devices supported	32
Data Type Supported	100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line
Scan Lines	100 input / 100 output
Physical Connections	DH+
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
	Recommended (not supplied): Belden 9463 Blue Hose®, 1 Pr #20 Str TC https://www.belden.com/

ELECTRICAL / ENVIRONMENTAL DC Input Voltage 12-24 VDC 3.83 Maximum Baud Rate 921.6K baud -40 C to 85 C **Operating Temperature** o o Οı Certification **CE** Approvals 02 **ENCLOSURE / HARDWARE** 5.40" x 3.83" x 1.19" Size Weight 7.6 oz Enclosure Type Anodized Aluminum Din rail or panel mount Mounting Power LED, DH+ Status LED & general purpose 6.4 LEDs LEDs on side **GATEWAY FEATURES & FUNCTIONS** Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule Alarming is triggered an email notification can be sent. You can configure up to 9 different users access to **Gateway Security** 0 0 diagnostic and configuration screens. Allows for data manipulation during protocol **Translation Table** translation. Scaling and other data format changes can occur in the gateway. NOT EXACTLY WHAT YOU WERE LOOKING FOR? Protocol specific status, counters, and error Real Time Automation offers a full line of gateway products. messages are accessible within the gateway's Status and Counters Give us a call at 1-800-249-1612. Or, check out a listing at diagnostics page. They can also be delivered to a www.rtautomation.com/products. We also offer connected device. customizations for unique applications. Allows users to see and log start up sequences, **Diagnostic Logging Page** protocol specific messages & error messages.

CATALOG #	DESCRIPTION
460ECDHM-D2E	Connects up to 32 EtherNet/IP adapters with as many as 32 DH+ devices













ALWAYS IN STOCK

MADE IN THE USA

EXPERT SUPPORT

5-YEAR WARRANTY

EMPLOYEE OWNED

Real Time Automation, Inc.

solutions@rtautomation.com