

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460ECMM-NNA4

EtherNet/IP to Modbus RTU Server

FEATURES

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Fully configurable Modbus RTU Client
- Connects up to 32 Modbus RTU Servers
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect EtherNet/IP Adapter Devices to Modbus RTU Servers

The 460ECMM moves registers and coils between Modbus RTU Server devices and an EtherNet/IP network of adapter devices. It's the perfect tool to tie in all of your EtherNet/IP devices into your Modbus RTU network. Easily interface existing device networks without having to add a controller.

How Do I Use the 460ECMM-NNA4 in My Application?

For most applications, the mapping is very straightforward. Modbus register and coil data is mapped to up 496 bytes of EtherNet/IP data per adapter. EtherNet/IP IO data is mapped directly to your Modbus RTU Server registers and coils. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

ETHERNET/IP SCANNER FEATURES			
Operation Mode	Class 1 I/O Scanner		
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported		
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double		
Maximum EtherNet/IP Adapter Devices	32		
Max Data Per Adapter Connection	Up to 496 bytes in each direction		
Maximum IO Scan Rate	50 msec		
MODBUS RTU CLIENT FEATURES			
Operation Mode	Modbus RTU Client		
Function Codes Supported	1,2,3,4,5,6, 15 & 16		
Swapping	Byte and Word Swapping		
Maximum Modbus RTU Server Devices	32		
Number Read/Write Scan Lines per RTU Server Device	200 Total - 100 reads & 100 writes		
Scan Line Support	Up to 125 Registers or 512 Coils		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
Manual			

ELECTRICAL / ENVIRONMENTA	L		
DC Input Voltage	12-24 VDC		
Maximum Baud Rate	115K baud	DIN Rail Mount	
Operating Temperature	-40 C to 85 C	3.88	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	,	
ENCLOSURE / HARDWARE			
Size	3.88" x 2.57" x 1.06"		
Weight	5.5 oz		
Enclosure Type	Anodized Aluminum	2.57	
Mounting	Din rail or panel mount		
LEDs	Power LED & 2 general purpose LEDs on side	Note: All dimensions	
GATEWAY FEATURES & FUNCT	TIONS	are in Inches	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on		
	any data moving through the gateway. If alarm rule is triggered an email notification can be sent.		
Gateway Security	You can configure up to 9 different users access to		
	diagnostic and configuration screens.		
	Allows for data manipulation during protocol		
Translation Table	translation. Scaling and other data format changes can occur in the gateway.		
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at <u>www.rtautomation.com/products</u> . We also offer customizations for unique applications.	
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.		

CATALOG #	DESCRIPTION				
460ECMM-NNA4	Connects up to 32 EtherNet/IP adapters with as many as 32 Modbus RTU Server devices				
Æ		Roc	WARRANTY	ij	

READY TO SHIP

Real Time Automation, Inc.

ALWAYS IN STOCK

solutions@rtautomation.com

5-YEAR WARRANTY

ENGINERD SUPPORT

EMPLOYEE OWNED