

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460ECMS-N34

EtherNet/IP to Modbus TCP/IP Client

FEATURES

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Fully configurable Modbus TCP/IP server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus TCP/IP client
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect EtherNet/IP Adapter Devices to a Modbus TCP/IP Client

The 460ECMS moves data between up to 32 EtherNet/IP and a Modbus TCP/IP client. With the 460ECMS, you now have a great tool to integrate newer EtherNet/IP devices into your Modbus TCP/IP systems. Perfect for interfacing to legacy Modbus controller and a great way to utilize a low cost Modbus logging solution on your EtherNet/IP devices.

How Do I Use the 460ECMS-N34 in My Application?

Up to 496 bytes of EtherNet/IP data can be mapped in each direction from up to 32 devices. Once the data is manually entered for each EtherNet/IP connection the data is automatically mapped by the gateway to Modbus TCP/IP. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

ETHERNET/IP SCANNER FEATURES	
Operation Mode	Class 1 I/O Scanner
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double
Maximum EtherNet/IP Adapter Devices	32
Max Data Per Adapter Connection	Up to 496 bytes in each direction
Maximum IO Scan Rate	50 msec
MODBUS TCP SERVER FEATURES	
Operation Mode	Modbus TCP/IP Server
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus TCP/IP Client Connections	10
Contiguous Data Areas	200 Total - 100 reads & 100 writes
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA			
Maximum Baud Rate	115K baud		EOs	
Operating Temperature	-40 C to 85 C			
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	ζ]		Port 1 00000
ENCLOSURE / HARDWARE		3.25		
Size	4.2" x 3.25" x 1"	3.25		
Weight	7 oz			2000 0000 0000 0000 0000 0000 0000 000
Enclosure Type	Anodized Aluminum			
Mounting	Din rail or panel mount			
LEDs	Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side	1.00	4.19	1.00
GATEWAY FEATURES & FUNCTION	ONS	Din Rail		
	Set <, <=, >, >=, ==, !=, and change-of-state rules on	Unit tun		_
Alarming	any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Panel Mount		
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.			
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.			
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.		offers a full line of	of gateway products. check out a listing at . We also offer
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.			

CATALOG #	DESCRIPTION
460ECMS-N34	Connects up to 32 EtherNet/IP adapters with a Modbus TCP client













Real Time Automation, Inc.

solutions@rtautomation.com