460ECPS-N2E

EtherNet/IP to PROFINET IO

FEATURES

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Fully configurable PROFINET device
- Supports up to 1280 bytes of data in each direction on PROFINET
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect EtherNet/IP Adapters to a PROFINET IO Controller

The 460ECPS moves data between up to 32 EtherNet/IP adapters and a PROFINET IO controller. It's the perfect tool to connect EtherNet/IP devices into your PROFINET controller.

Best of all, the product is made in the USA and comes with 5-year warranty.

How Do I Use the 460ECPS-N2E in My Application?

EtherNet/IP data will be mapped into 10 PROFINET slots. The gateway can move up 1280 bytes of data in each direction.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

ETHERNET/IP SCANNER FEATURES		
Operation Mode	Class 1 I/O Scanner	
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported	
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double	
Maximum EtherNet/IP Adapter Devices	32	
Max Data Per Adapter Connection	Up to 496 bytes in each direction	
Maximum IO Scan Rate	50 msec	
PROFINET SERVER FEATURES		
Maximum Number of Slots	10 Slots in, 10 Slots out	
Slot Data Segment Sizes	8, 16, 32, 64 or 128 Bytes	
Each Slot Can be Defined for a Single Data Type	Int8, int16, int32, int64, UInt8, Uint16, Uint32, Uint64, float, double, binary8, binary16 or binary32,	
of	Short String	
Total Data Supported in Each Direction	1280 Bytes	
Maximum Profinet IO Controller Connections	1	
String Support	1 string per slot	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software - automatically locates RTA	Unlimited firmware feature upgrades for life	
gateway on the network	Offinition filling of catalog appliances for inc	
CAT5 crossover cable for direct connection to PC	Complete, unlimited access to our industry leading support staff	
during programming	Complete, ariminica access to our mausity reading support start	
Manual		

ELECTRICAL / ENVIRONMENTA	AL .	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	□ (⊗ 🛰
Operating Temperature	-40 C to 85 C	=
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	3.83
ENCLOSURE / HARDWARE		0 0 1 0 0 m
Size	5.40" x 3.83" x 1.19"	
Weight	7.6 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	
GATEWAY FEATURES & FUNCTIONS		
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460ECPS-N2E	Connects up to 32 EtherNet/IP adapters with a PROFINET IO controller













MADE IN THE USA

EXPERT SUPPORT 5-YEAR WARRANTY

EMPLOYEE OWNED