# 460ESMM-N700

## EtherNet/IP to Modbus RTU Servers

# **FEATURES**

- Fully configurable
   EtherNet/IP adapter
- Up to 480 bytes in each direction per adapter connection
- Fully configurable Modbus RTU Client
- Connects up to 32
   Modbus RTU Servers
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warrantv

#### Connect Modbus RTU Servers to an EtherNet/IP Scanner

The 460ESMM connects up to 32 Modbus RTU Servers to an EtherNet/IP controller. It's the perfect tool to save legacy Modbus RTU devices from the scrap pile and utilize the huge variety of Modbus RTU devices available in your EtherNet/IP architectures.

Best of all, the product is made in the USA and comes with 5-year warranty.

## How Do I Use the 460ESMM-N700 in My Application?

Modbus register and coil data is mapped to EtherNet/IP IO data blocks. EtherNet/IP data is mapped directly to your Modbus RTU Servers. Up to 480 bytes of data can be moved in each direction between Modbus RTU and EtherNet/IP. It really is that simple.

### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

# **Specification**

ETHERNET/IP ADAPTER FEATURES		
Operation Mode	Class 1 I/O Adapter	
Message Support	Implicit Class 1 Cyclic I/O, Explicit Class 3 and UCMM Supported	
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double	
Maximum EtherNet/IP Scanner Devices	Up to 10 can listen, only 8 can write I/O	
Maximum Data Supported	Up to 480 bytes in each direction per adapter connection	
Maximum IO Scan Rate	20 msec	
MODBUS RTU CLIENT FEATURES		
Operation Mode	Modbus RTU Master	
Function Codes Supported	1,2,3,4,5,6, 15 & 16	
Swapping	Byte and Word Swapping	
Maximum Modbus RTU Slave Devices	32	
Number Read/Write Scan Lines per RTU Slave Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 125 Registers or 512 Coils	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	Imerinet 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
ENCLOSURE / HARDWARE		
Size	4.19" x 3.25" x 1"	3,26
Weight	6.5 oz	
Enclosure Type	Anodized Aluminum	Note: All dimension are numbers
Mounting	Din rail or panel mount	are n inches
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	-1.00
<b>GATEWAY FEATURES &amp; FUNCTION</b>	IS	Din Rail
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Panel Mount
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	• •••
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR?  Real Time Automation offers a full line of gateway products.  Give us a call at 1-800-249-1612. Or, check out a listing at  www.rtautomation.com/products. We also offer  customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

	CATALOG #	DESCRIPTION
	460ESMM-N700	Connects an EtherNet/IP scanner with as many as 32 Modbus RTU Servers













MADE IN THE USA

EXPERT SUPPORT

**EMPLOYEE OWNED**