460ESSC-N700

EtherNet/IP to Siemens S7 PLC

FEATURES

- Fully configurable EtherNet/IP adapter
- Up to 480 bytes in each direction per adapter connection
- Supports connections to five Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Get Your EtherNet/IP Scanner Connected Directly to Your S7 PLC

The 460ESSC moves data between an EtherNet/IP scanner device and up to five S7 PI Cs.

Move data from your EtherNet/IP scanner device to S7 PLCs like the S7 300/400/1200/1500.

How Do I Use the 460ESSC-N700 in My Application?

You allocate two memory blocks in your S7 PLC. One area is a user-defined set of output addresses sending data to your EtherNet/IP scanner. The other is input only data receiving data from your EtherNet/IP scanner.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

ETHERNET/IP ADAPTER FEATURES	
Operation Mode	Class 1 I/O Adapter
Message Support	Implicit Class 1 Cyclic I/O, Explicit Class 3 and UCMM Supported
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double
Maximum EtherNet/IP Scanner Devices	Up to 10 can listen, only 8 can write I/O
Maximum Data Supported	Up to 480 bytes in each direction per adapter connection
Maximum IO Scan Rate	20 msec
Siemens S7 CLIENT FEATURES	
PLC Support	S7 300/400/1200/1500
Maximum Number of PLCs Supported	5
Maximum Number of Inputs/Outputs per PLC	150
Maximum Number of Bytes per Scan Line	400
Memory Area Access	Input (I), Output (Q), and Data Block(DB)
Supported Data Types	8 Bit Int, 16 Bit Int, 32 Bit Int, 32 Bit Float, Bool and Char Array
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

ELECTRICAL / ENIVIRONMACNICA	1	
ELECTRICAL / ENVIRONMENTA	_	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	Internet
ENCLOSURE / HARDWARE		
Size	4.19" x 3.25" x 1"	3.25
Weight	6.5 oz	
Enclosure Type	Anodized Aluminum	Moter Alidimension of Signature in nones
Mounting	Din rail or panel mount	are in inches
LED-	Power LED, Ethernet link/data LED, & Ethernet	
LEDs	speed LED	1.001.00
GATEWAY FEATURES & FUNCT	TIONS	Din Rail
	Set <, <=, >, >=, ==, !=, and change-of-state rules on	Din Raii
Alarming	any data moving through the gateway. If alarm rule	
	is triggered an email notification can be sent.	Panel Mount
Gateway Security	You can configure up to 9 different users access to	Panel Mount
	diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol	
	translation. Scaling and other data format changes	
Translation Table		
	can occur in the gateway.	NOT EVACTIVAMILAT VOLUMERE LOOKING FOR
Status and Counters	Protocol specific status, counters, and error	NOT EXACTLY WHAT YOU WERE LOOKING FOR?
	messages are accessible within the gateway's	Real Time Automation offers a full line of gateway products.
	diagnostics page. They can also be delivered to a	Give us a call at 1-800-249-1612. Or, check out a listing at
	connected device.	www.rtautomation.com/products. We also offer
		customizations for unique applications.
	Allows were to see and les start up servences	
Diagnostic Logging Page	Allows users to see and log start up sequences,	
- 55 5 5	protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460ESSC-N700	Connects an EtherNet/IP scanner with as many as five S7 PLCs









