

## Interconnect Up to Five Allen-Bradley PLCs

### FEATURES

- Supports connection to five Allen-Bradley PLCs
- Up to 150 tag or file arrays of data can be mapped in each direction
- Effortless Browser Based Configuration, no programming software is required
- 5-Year Hardware Warranty

### Connect Up to Five Allen-Bradley PLCs

The 460ETC can move data between up to five Allen-Bradley PLCs using connected and unconnected messaging.  
Best of all, the product comes with 5-year warranty.


### How Do I Use the 460ETC-N2E in My Application?

The 460ETC allows you to not only map, but also manipulate your data while moving it between PLCs.  
It really is that simple..

### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.


When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



**A Solution, A Philosophy, the RTA Way.** We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: **To move your data where you need it, when you need it, and how you need it.**

ETHERNET TAG CLIENT FEATURES		
PLC Support		ControlLogix, CompactLogix, FlexLogix, MicroLogix, SLCs and PLC5Es
Maximum Number of PLCs Supported		5
Maximum Number of Input/Output Tags or Files per PLC		150
Maximum Number of Bytes per PLC Tag		400
Array Support		Yes, for all data types except strings
Supported Data Types		Usint, Sint, Uint, Int, Uuint, Dint, Real, String, Bit Array 16, Bit Array 32, Bool, and Long

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage		12-24 VDC
Maximum Baud Rate		115K baud
Operating Temperature		-40 C to 85 C
Certification		RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2
ENCLOSURE / HARDWARE		
Size		5.40" x 3.83" x 1.19"
Weight		7.6 oz
Enclosure Type		Anodized Aluminum
Mounting		Din rail or panel mount
LEDs		Power LED & 2 general purpose LEDs on side
INCLUDED WITH GATEWAY		
3' Power Cable with Flying leads		Manual
Complete, Unlimited Access to our Industry Leading Support Staff.		5 Year Hardware Warranty
IPSetup software – Automatically locates RTA Gateway on the		Unlimited Firmware Feature Upgrades for Life



CATALOG #	DESCRIPTION	
4605TCN2E	Connect up to five Allen-Bradley PLCs	<p>NOT EXACTLY WHAT YOU WERE LOOKING FOR?</p> <p>Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at <a href="http://www.rtautomation.com/products">www.rtautomation.com/products</a>. We also offer customizations for unique applications.</p>
4605TCN2E	4605TCN2E power cable for direct connection to PC during programming	



ALWAYS IN STOCK



READY TO SHIP



ENGINEERD SUPPORT



5-YEAR WARRANTY



EMPLOYEE OWNED