# 460ETCAWS-N2E

## Allen-Bradley PLC to Amazon Web Services (AWS)

## **FEATURES**

- Supports connection to five Allen-Bradley PLCs
- Up to 150 tag or file arrays of data can be mapped in each direction
- AWS Certified Product
- Allows factory floor based devices to move its data to IT
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

#### **Connect Five A-B PLCs to AWS IoT Core**

The 460ETCAWS moves data between up to five Allen-Bradley PLCs and the AWS platform. Allowing you to easily log data and leverage in populating dashboards. Best of all, the product comes with 5-year warranty.

### How Do I Use the 460ETCAWS-N2E in My Application?

Tag or file data from the data table of your PLC is mapped directly to topics in AWS. Access the PLC data with no alteration to the PLC program. SSL transport layer security protects the data moving from your operations network to the cloud.

## Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

# **Specification**

ETHERNET TAG CLIENT FEATURES	
PLC Support	ControlLogix, CompactLogix, FlexLogix, MicroLogix, SLCs and PLC5Es
Maximum Number of PLCs Supported	5
Maximum Number of Input/Output Tags or Files per PLC	150
Maximum Number of Bytes per PLC Tag	400
Array Support	Yes, for all data types except strings
Supported Data Types	Usint, Sint, Uint, Int, Udint, Dint, Real, String, Bit Array 16, Bit Array 32, Bool, and Long
MQTT CLIENT FEATURES	
Operation Mode	Amazon Web Services (AWS)
Max Broker Connections	1 AWS
Max Data Points Per Connection	250 Read Topics, 250 Write Topics
Security	SSL certificate based cloud access
Supported Data Formats	JSON
Data Payload	Topic Name and Value
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

DC Input Voltage  Maximum Baud Rate Operating Temperature  Certification  Certification  ENCLOSURE / HARDWARE Size  5.40" x 3.83" x 1.19"  Weight  7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount LEDs  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-st any data moving through the gateway. I is triggered an email notification can be	
Operating Temperature  -40 C to 85 C  RoHS-Compliant, UL, CUL, CE Appro I Div 2  ENCLOSURE / HARDWARE Size  5.40" x 3.83" x 1.19"  Weight  7.6 oz  Enclosure Type  Anodized Aluminum  Mounting  LEDs  Power LED & 2 general purpose LED:  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-st any data moving through the gateway. I	
Certification  ROHS-Compliant, UL, CUL, CE Approl I Div 2  ENCLOSURE / HARDWARE  Size  5.40" x 3.83" x 1.19"  Weight  7.6 oz  Enclosure Type  Anodized Aluminum  Mounting  Din rail or panel mount  LEDs  Power LED & 2 general purpose LED:  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-st any data moving through the gateway. I	
ENCLOSURE / HARDWARE Size 5.40" x 3.83" x 1.19" Weight 7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount LEDs Power LED & 2 general purpose LED: GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-st any data moving through the gateway. I	
Size 5.40" x 3.83" x 1.19"  Weight 7.6 oz  Enclosure Type Anodized Aluminum  Mounting Din rail or panel mount  LEDs Power LED & 2 general purpose LED:  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-st any data moving through the gateway. I	
Weight 7.6 oz  Enclosure Type Anodized Aluminum  Mounting Din rail or panel mount  LEDs Power LED & 2 general purpose LED:  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-st any data moving through the gateway. I	
Enclosure Type  Mounting  LEDs  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-st any data moving through the gateway. I	
Mounting  LEDs  Din rail or panel mount Power LED & 2 general purpose LED:  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==,!=, and change-of-st any data moving through the gateway. I	
LEDs Power LED & 2 general purpose LED:  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-st any data moving through the gateway. I	
GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-st any data moving through the gateway. I	
Set <, <=, >, >=, ==, !=, and change-of-st Alarming any data moving through the gateway. I	s on side
Alarming any data moving through the gateway. I	
is triggered an email nouncation can be	If alarm rule
Gateway Security  You can configure up to 9 different use diagnostic and configuration screens.	ers access to
Allows for data manipulation durin translation Table translation. Scaling and other data form can occur in the gateway.	
Protocol specific status, counters, messages are accessible within the diagnostics page. They can also be del connected device.	Real Time Automation offers a full line of gateway products.
Diagnostic Logging Page  Allows users to see and log start up protocol specific messages & error mess	sequences,

CATALOG #	DESCRIPTION
460ETCAWS-N2E	Easily and securely connect Allen-Bradley PLCs to Amazon Web Services (AWS) IoT Core









