## **460ETCBMS-N700**

## **BACnet MS/TP to Allen-Bradley PLC**

## **FEATURES**

- Supports connection to five Allen-Bradley PLCs
- Up to 150 tag or file arrays of data can be mapped in each direction
- Fully configurable BACnet MS/TP Subordinate
- BACnet MS/TP supports device, binary I/O, analog I/O, and character string value object types
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

# Get Your BACnet MS/TP System Connected Directly to the Data Table of Your Allen-Bradley PLC

The 460ETCBMS moves data between a BACnet MS/TP system and Allen-Bradley PLCs.

With the 460ETCBMS, you are making a direct connection between BACnet MS/TP Manager data and user-defined tags or registers in the data table of your Allen-Bradley PLCs. There is no polling from the PLC or EtherNet/IP scan lists to arrange.

### How Do I Use the 460ETCBMS-N700 in My Application?

You allocate two blocks in your Allen-Bradley PLC. One area is write only tags or register blocks accepting data from your BACnet MS/TP Manager. The other area is read only tags or register blocks to send data to your BACnet MS/TP Manager. It's really that simple.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

## **Specification**

ETHERNET TAG CLIENT FEATURES			
	Controll aniv Comment only Floridania Missal only CLCs and DLCFFs		
PLC Support	ControlLogix, CompactLogix, FlexLogix, MicroLogix, SLCs and PLC5Es		
Maximum Number of PLCs Supported	5		
Maximum Number of Input/Output Tags or Files per PLC	150		
Maximum Number of Bytes per PLC Tag	400		
Array Support	Yes, for all data types except strings		
Supported Data Types	Usint, Sint, Uint, Int, Udint, Dint, Real, String, Bit Array 16, Bit Array 32, Bool, and Long		
BACNET MS/TP RESPONDER FEATURES			
Operation Mode	BACnet MS/TP Manager Responder		
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value		
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B		
Maximum Connections	1		
Analog Objects Supported	1200 Input and 1200 Output		
Binary Objects Supported	1600 Input and 1600 Output		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
Manual			

ELECTRICAL / ENVIRONMENTA	AL .		
DC Input Voltage	12-24 VDC		
Maximum Baud Rate	115K baud		
Operating Temperature	-40 C to 85 C		
Certification	RoHS-Compliant, UL, CUL, CE Approvals	Internet S	
ENCLOSURE / HARDWARE			
Size	4.19" x 3.25" x 1"	3,26	
Weight	6.5 oz	Note: All dimension are n inches	
Enclosure Type	Anodized Aluminum	Note: All dimension	
Mounting	Din rail or panel mount	are n inches	
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	-1.00	
GATEWAY FEATURES & FUNCTIONS		Dia Dail	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Din Rail Panel Mount	
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	•	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.		
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR?  Real Time Automation offers a full line of gateway products.  Give us a call at 1-800-249-1612. Or, check out a listing at  www.rtautomation.com/products. We also offer  customizations for unique applications.	
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.		

CATALOG #	DESCRIPTION
460ETCBMS-N700	Connects up to five Allen-Bradley PLCs with a BACnet MS/TP Manager









