CONTACT US!

1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460ETCBS-NNA4

BACnet/IP to Allen-Bradley PLC

FEATURES

- Supports connection to 5 Allen-Bradley PLCs
- Up to 150 Tag or File Arrays of data can be mapped in each direction
- Fully Configurable BACnet/IP Server
- BACnet/IP Supports
 Device, Binary I/O,
 Analog I/O, and
 Character String
 Value Object Types
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Connect Allen-Bradley PLCs to BACnet/IP

The 460ETCBS moves data between a BACnet/IP Building Management System (BMS) and one to five Allen-Bradley PLCs.

With the 460ETCBS, you are making a direct connection between BACnet/IP data and user-defined tags or files in the data table of your Allen-Bradley PLC. There is no polling from the PLC or EtherNet/IP scan lists to arrange.



How do I use the 460ETCBS-NNA4 in my application?

You allocate two blocks in your Allen-Bradley PLC. One area is write only tags or register blocks accepting data from BACnet/IP. The other is read only tags or register blocks to send data to your BACnet/IP BMS.

It's really that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.

Try the RTA difference today! Call us at 800-249-1612 or check out our solutions at rtautomation.com

A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience, all the better. Thirty years later, our mission remains the same: to move your data where you need it, when you need it and how you need it.

Specification

Ethernet Tag Client FEATURES					
PLC Support		ControlLogix, CompactLogix, Fle	ControlLogix, CompactLogix, FlexLogix, MicroLogix, SLCs and PLC5Es		
Maximum Number of PLCs Supported		5			
Maximum Number of Input Tags or Files per PLC		150			
Maximum Number of Output Tags or Files per PLC		150			
Array Support		Yes, for all data types except strings			
Supported Data Types		ControlLogix/CompactLogix/FlexLogix: Bit, 32 Bit Array, SINT, INT, REAL, STRING, DINT, MicroLogix/SLC/PLC5E: 16 Bit Array, INT, REAL, String			
BACnet/IP Server FEATURES		Ü	, , , , , , , , , , , , , , , , , , ,		
Operation Mode		BACnet/IP Server			
Supported Object Types		Device, Binary I/O, Analog I/O, C	Device, Binary I/O, Analog I/O, Character String Value		
Supported Service Codes		Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B			
Maximum Connections		1			
Analog Objects Supported		1200 Input and 1200 Output			
Binary Objects Supported		1600 Input and 1600 Output			
INCLUDED WITH GATEWAY					
3' power cable with flying leads		5-year hardware warranty			
IPSetup software – automatically locates RTA gateway on the network		Unlimited firmware feature upgrades for life			
CAT5 crossover cable for direct connection to PC during programming		Complete, unlimited access to our industry leading support staff			
Manual					
ELECTRICAL / ENVIRONMENTAL					
DC Input Voltage	12-24 VDC				
Maximum Baud Rate	115K baud		DIN Rail Mount		
Operating Temperature	-40 C to 85 C		3.88		
Certification	RoHS-Compl	liant, UL, CUL, CE Approvals			
ENCLOSURE / HARDWARE					
Size	3.88" x 2.57" x 1.06"				
Weight	5.5 oz				
Enclosure Type	Anodized Alu	minum	2.57		
Mounting	Din rail or panel mount				
LEDs	Power LED & 2 general purpose LEDs on side		Note: All dimensions		
GATEWAY FEATURES & FUNCTIO	ONS		are in Inches		

Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	996
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	1.06
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WE Real Time Automation offers a full li Give us a call at 1-800-249-1612. C www.rtautomation.com/produ customizations for unique
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages	

		00000	
	1.06	w	
		•	
Γim us	e Au a ca /w.rt	CTLY WHAT YOU WERE LOOKING atomation offers a full line of gateway II at 1-800-249-1612. Or, check out a cautomation.com/products. We also obstomizations for unique applications.	products. listing at

CA	ATALOG #	DESCRIPTION
46	0ETCBS-NNA4	Connects up to five Allen-Bradley PLCs with a BACnet/IP client

Made in the

Always In Stock

Ready to





