

REAL TIME AUTOMATION, INC. N26W23315 Paul Road, Pewaukee, WI 53072 800.249.1612 | solutions@rtautomation.com

460ETCSM-NNA1

REAL TIME AUTOMATION GATEWAY Allen-bradley PLC to SNMP

KEY FEATURES

- Supports connection to five Allen-Bradley PLCs
- Up to 150 tag or file arrays of data can be mapped in each direction
- Get data directly from SNMP enabled devices
- Support for SNMPv1 & SNMPv2c
- Effortless browser-based configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-year hardware warranty

Connect your Allen-Bradley PLC to SNMP enabled devices

The 460ETCSM moves data between Allen-Bradley PLCs and SNMP Agents. With support for SNMPv1 and SNMPv2C it has never been easier to bring data from all your SNMP enabled network devices to your factory floor. Best of all, the product comes with 5-year warranty.

How Do I Use the 460ETCSM-NNA1 in My Application?

Data from your SNMP Agent device is written directly into tags in your Allen-Bradley PLC. Receive SNMP trap information with up to 10 variable bindings. Use a PC based tool to find and display all available Object Identifiers, then export to a file to be imported into the gateway and used for configuration.



Why Use RTA As Your Gateway Supplier?

Other companies might offer protocol gateways, but nobody matches the support and service you'll get from RTA. When you call, a real person picks up the phone. Sales gives you straight answers and solid recommendations. And when you need support, you'll talk to an engineer who helped build the product—no tickets, no waiting, just real help, right away.

🍠 800.249.1612



REAL TIME AUTOMATION, INC.

N26W23315 Paul Road, Pewaukee, WI 53072 800.249.1612 | solutions@rtautomation.com

ALLEN-BRADLEY PLC FEATURE	S			
PLC Support		ControlLogix, Compact	tLogix, FlexLo	ogix, MicroLogix, SLCs and PLC5Es
Maximum Number of PLCs Supported		5		
Maximum Number of Input/Output Tags or Files per PLC		150		
Maximum Number of Bytes per PLC Tag		400		
Array Support		Yes, for all data types except strings		
Supported Data Types		Usint, Sint, Uint, Int, Udint, Dint, Real, String, Bit Array 16, Bit Array 32, Bool, and Long		
SNMP MANAGER FEATURES				
Operation Mode		SNMP Manager		
SNMP Version Support		SNMPv1, SNMPv2c		
Maximum Agents Supported		32		
Maximum Read/Write OIDs per Agent		100		
Supported Get Data Types		Counter32, Gauge32, Integer, IP Address, Octet String, OID, TimeTicks		
Supported Set Data Types		Gauge32, Integer, Octet String		
NCLUDED WITH GATEWAY				
3' power cable with flying leads			5-year hardware warranty	
IPSetup software – automatically locates RTA gatew		ay on the network Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC du		ring programming Complete, unlimited access to our industry leading support staff		
ELECTRICAL / ENVIRONMENTA	۱L			
DC Input Voltage	12-24 VDC			DIN Rail Mount
Maximum Baud Rate	115K baud			3.88
Operating Temperature	-40 C to 85 C			
Certification	RoHS-Compliar	nt, UL, CUL, CE Approvals	S	
ENCLOSURE / HARDWARE				
Size	3.88" x 2.57" x 1.06"			2.57
Weight	5.5 oz			
Enclosure Type	Anodized Alum	inum		Note: All dimensions are in Inches
Mounting	Din rail or pane			
LEDs		general purpose LEDs or	n side	0000
GATEWAY FEATURES & FUNCT		8		
Alarming	Set <, <=, >, >=, =	=, !=, and change-of-state ru ugh the gateway. If alarm ru ion can be sent.		
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.			
Translation Table	Allows for data manipulation during protocol translation Scaling and other data format changes can occur in the gateway.			
Status and Counters	accessible within	status, counters, and error m the gateway's diagnostics pa to a connected device.		NOT EXACTLY WHAT YOU WERE LOOKING FOR? RTA offers a full line of gateway products. Give us a call at 1-800-249-1612 or visit www.rtautomation.com/products.
Diagnostic Logging Page		ee and log start up sequence & error messages.	es, protocol	We also offer customizations for unique applications.
CATALOG #	DESCRI			
460ETCSM-NNA1	TCSM-NNA1 Connect up to five Allen-Bradle		PLCs to up to	o 32 SNMP Agents

ALWAYS IN STOCK

Contact us:

2 800.249.1612

READY TO SHIP

Solutions@rtautomation.com

5-YEAR WARRANTY

ENGINERD SUPPORT

www.rtautomation.com

BREWED IN WISCONSIN

EMPLOYEE OWNED