

CONTACT US! 1-800-249-1612 rtautomation.com

460MCBM-N34

Modbus TCP/IP to BACnet MS/TP

FEATURES

- Fully configurable Modbus TCP/IP client
- Connects up to 32
 Modbus TCP/IP
 servers
- Fully configurable BACnet MS/TP Manager
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect Modbus TCP/IP Servers to BACnet MS/TP Devices

The 460MCBM moves data between a network of up to 32 Modbus TCP/IP servers and up to 32 BACnet MS/TP devices.

It's a perfect tool to move data between your Modbus power meters, boilers, chillers, and other server devices and your BACnet MS/TP devices.

How Do I Use the 460MCBM-N34 in My Application?

For most applications, the mapping is very straightforward. Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to binary objects. The only additional piece required for BACnet is adding metadata to each object. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



TCP/IP Servers



460MCBM-N34



MS/TP Subordinates

A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

MODBUS TCP CLIENT FEATURES	
Operation Mode	Modbus TCP/IP Client
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus TCP/IP Server Devices	32
Number Read/Write Scan Lines per Server Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 125 Registers or 512 Coils
BACNET MS/TP MANAGER FEATURES	
Operation Mode	BACnet MS/TP Manager Initiator
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A
Maximum Connections	32
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 128 Objects
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA			
Maximum Baud Rate	115K baud	LE	Os	
			1	
Operating remperature		↓ <i>μ</i> −−−1		- B A
Certification	I Div 2	<u>6</u>		Port
ENCLOSURE / HARDWARE		aar 0		۵ (۵)
Size	4.2" x 3.25" x 1"	3.25		
Weight	7 oz			e e e
Enclosure Type	Anodized Aluminum			Pero
Mounting	Din rail or panel mount			
LEDs	Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side	1.00	4.19	1.00
GATEWAY FEATURES & FUNCTI	IONS	Din Bail		
	Set <, <=, >, >=, ==, !=, and change-of-state rules on	C		-
Alarming	any data moving through the gateway. If alarm rule			
-	is triggered an email notification can be sent.	Panel Mount		—
	You can configure up to 9 different users access to			
Gateway Security	diagnostic and configuration screens.			
	Allows for data manipulation during protocol			
IDW 2 VCLOSURE / HARDWARE ze 4.2" x 3.25" x 1" eight 7 oz Anodized Aluminum ounting Din rail or panel mount EDs Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side ATEWAY FEATURES & FUNCTIONS Set <, <=, >, >=, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. arming You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. atus and Counters Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY				
	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2 LOSURE / HARDWARE 4.2" x 3.25" x 1" ght 7 oz Dosure Type Anodized Aluminum nting Din rail or panel mount Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side EWAY FEATURES & FUNCTIONS Set <, <=, >=, =, =, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. way Security You can configure up to 9 different users access to diagnostic and configuration screens. slation Table Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. us and Counters Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a comported dwice NOT EXACTLY WHAT			
	Protocol specific status counters and error	NOT EXACTLY W	HAT YOU WERE	LOOKING FOR?
	•	Real Time Automation	offers a full line of	f gateway products
Status and Counters	с			
		· · · · · · · · · · · · · · · · · · ·		
		customizati	ons for unique app	olications.
Diagnostic Logging Page	Allows users to see and log start up sequences,			
	protocol specific messages & error messages.			

Connects up to 32 Modbus TCP servers with as many as 32 BACnet	CATALOG # DESCRIPTION		TION	ALOG #
MS/TP Subordinates	bUWU BWI-N34	h as many as 32 BAC:		/ICBM-N34









Real Time Automation, Inc.

solutions@rtautomation.com