460MCBS-N2EW

Modbus TCP/IP Servers to BACnet/IP

FEATURES

- Fully configurable Modbus TCP/IP client
- Connects up to 32 Modbus TCP/IP servers
- Fully configurable BACnet/IP server
- BACnet/IP supports device, binary I/O, analog I/O, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect Modbus TCP/IP Servers to a BACnet/IP Client

The 460MCBS moves data between up to 32 Modbus TCP/IP servers and a BACnet/IP Building Automation System (BAS). It's a perfect tool to tie Modbus power meters, boilers, chillers, and other devices into your BACnet/IP building automation system over Wi-Fi using Wi-Fi IEEE 802.11 b/g/n at 2.4GHz with AES encryption 128-bit.

Best of all, the product comes with 5-year warranty.

How Do I Use the 460MCBS-N2EW in My Application?

For most applications, the mapping is very straightforward. Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to binary objects. The only additional piece required for BACnet is adding metadata to each object. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

Operation Mode	Modbus TCP/IP Client	
Function Codes Supported	1,2,3,4,5,6, 15 & 16	
Swapping	Byte and Word Swapping	
Maximum Modbus TCP/IP Server Devices	32	
Number Read/Write Scan Lines per Server Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 125 Registers or 512 Coils	
BACNET IP SERVER FEATURES		
Operation Mode	BACnet/IP Server	
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value	
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B	
Maximum COV Subscriptions	2800	
Analog Objects Supported	1200 Input and 1200 Output	
Binary Objects Supported	1600 Input and 1600 Output	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENTA	_	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	(s PD_3
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	3.83
ENCLOSURE / HARDWARE		
Size	5.40" x 3.83" x 1.19"	
Weight	7.6 oz	⊕
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	
GATEWAY FEATURES & FUNCTIONS		
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	. 5.40
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460MCBS-N2EW	Connects up to 32 Modbus TCP servers with a BACnet/IP client









