

CONTACT US! 1-800-249-1612 rtautomation.com

### **Real Time Automation Gateways**

## **460MCMS-N2E**

### Modbus TCP/IP Data Manipulation

## **FEATURES**

- Fully configurable Modbus TCP/IP client
- Connects up to 32 Modbus TCP/IP servers
- Fully configurable Modbus TCP/IP server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus TCP/IP client
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

# Manipulate Modbus TCP/IP Server Data Moving to a Modbus TCP/IP Client

The 460MCMS moves data between up to 32 Modbus TCP/IP server devices and a Modbus TCP/IP client.

With the 460MCMS, register and coil data can freely move between any devices connected to the gateway.

#### How Do I Use the 460MCMS-N2E in My Application?

The 460MCMS is designed for those times when you have to manipulate your data, slow down the flow of data, or allow a client to handle more servers than it supports. The 460MCMS allows you to add scaling to data, apply math operations, add alarming, and control the request speeds of your server devices. It can also concatenate multiple server devices into one device allowing your client to communicate with more devices.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

# **Specification**

| MODBUS TCP CLIENT FEATURES  |  |
|---|--|
| Operation Mode  | Modbus TCP/IP Client   |
| Function Codes Supported  | 1,2,3,4,5,6, 15 & 16   |
| Swapping  | Byte and Word Swapping   |
| Maximum Modbus TCP/IP Server Devices                                | 32   |
| Number Read/Write Scan Lines per Server Device                      | 200 Total - 100 reads & 100 writes                               |
| Scan Line Support   | Up to 125 Registers or 512 Coils                                 |
| MODBUS TCP SERVER FEATURES  |  |
| Operation Mode  | Modbus TCP/IP Server   |
| Function Codes Supported  | 1,2,3,4,5,6, 15 & 16   |
| Swapping  | Byte and Word Swapping   |
| Maximum Modbus TCP/IP Client Connections                            | 10   |
| Contiguous Data Areas   | 200 Total - 100 reads & 100 writes                               |
| Data Area Limits  | 512 Contiguous Coils or 512 Contiguous Registers                 |
| INCLUDED WITH GATEWAY   |  |
| 3' power cable with flying leads                                    | 5-year hardware warranty   |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life                     |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff |
| Manual  |  |

| ELECTRICAL / ENVIRONMENTA          | L   |   |
|------------------------------------|---|---|
| DC Input Voltage                   | 12-24 VDC   |   |
| Maximum Baud Rate                  | 115K baud   |   |
| Operating Temperature              | -40 C to 85 C   |   |
| Certification                      | RoHS-Compliant, UL, CUL, CE Approvals, Class<br>I Div 2   | 3.83 - 1.19 -   |
| ENCLOSURE / HARDWARE               |   |   |
| Size                               | 5.40" x 3.83" x 1.19"   |   |
| Weight                             | 7.6 oz  |   |
| Enclosure Type                     | Anodized Aluminum   |   |
| Mounting                           | Din rail or panel mount   |   |
| LEDs                               | Power LED & 2 general purpose LEDs on side  |   |
| <b>GATEWAY FEATURES &amp; FUNC</b> | ΓIONS   |   |
| Alarming                           | Set <, <=, >, >=, ==, !=, and change-of-state rules on<br>any data moving through the gateway. If alarm rule<br>is triggered an email notification can be sent.         |   |
| Gateway Security                   | You can configure up to 9 different users access to diagnostic and configuration screens.   |   |
| Translation Table                  | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.   |   |
| Status and Counters                | Protocol specific status, counters, and error<br>messages are accessible within the gateway's<br>diagnostics page. They can also be delivered to a<br>connected device. | NOT EXACTLY WHAT YOU WERE LOOKING FOR?<br>Real Time Automation offers a full line of gateway products.<br>Give us a call at 1-800-249-1612. Or, check out a listing at<br><u>www.rtautomation.com/products</u> . We also offer<br>customizations for unique applications. |
| Diagnostic Logging Page            | Allows users to see and log start up sequences, protocol specific messages & error messages.  |   |

| CATALOG #   | DESCRIPTION   |
|-------------|---|
| 460MCMS-N2E | Connects up to 32 Modbus TCP servers with a Modbus TCP client |









**5-YEAR WARRANTY** 



Real Time Automation, Inc.

solutions@rtautomation.com