

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460MCTCP-NNA1

Ethernet TCP/IP to Modbus TCP/IP Server

FEATURES

- Fully configurable Modbus TCP/IP client
- Connects up to 32 Modbus TCP/IP servers
- Support up to 10 TCP/IP devices
- Parse & concatenate ASCII/HEX data in up to 50 segments by delimiter or offset
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Get Data from Modbus TCP/IP Servers into Your Ethernet TCP/IP Devices

The 460MCTCP moves data between up to 32 Modbus TCP/IP servers and an Ethernet TCP/IP device.

With the 460MCTCP, you have a tool to help you map Modbus TCP/IP device data into an Ethernet TCP/IP application. You can also capture Ethernet TCP/IP commands and write them to your Modbus TCP/IP server devices.

How Do I Use the 460MCTCP-NNA1 in My Application?

ASCII data is parsed and mapped directly to registers and coils in your Modbus TCP/IP servers. When writing from your Modbus TCP/IP servers, register and coil data will be grouped and delivered as an ASCII string. It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

MODBUS TCP CLIENT FEATURES				
Operation Mode	Modbus TCP/IP Client			
Function Codes Supported	1,2,3,4,5,6, 15 & 16			
Swapping	Byte and Word Swapping			
Maximum Modbus TCP/IP Server Devices	32			
Number Read/Write Scan Lines per Server Device	200 Total - 100 reads & 100 writes			
Scan Line Support	Up to 125 Registers or 512 Coils			
ETHERNET TCP/IP FEATURES				
Operation Mode	Client or Server			
Maximum Number of Devices Supported	10			
Maximum Number of Characters Transferred	1024			
Delimiter Processing	Incoming delimiters can be automatically removed; Outgoing delimiters automatically added if configured			
Parsing	Parse String of ASCII Data in up to 50 Segments by Delimiter or Offset			
Concatenation	Concatenate up to 50 segments/strings of ASCII data with optional delimiter			
INCLUDED WITH GATEWAY				
3' power cable with flying leads	5-year hardware warranty			
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life			
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff			
Manual				

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	DIN Rail Mount
Operating Temperature	-40 C to 85 C	3.88
Certification	RoHS-Compliant, UL, CUL, CE Approvals	,
ENCLOSURE / HARDWARE		
Size	3.88" x 2.57" x 1.06"	
Weight	5.5 oz	
Enclosure Type	Anodized Aluminum	2.57
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	Note: All dimensions
GATEWAY FEATURES & FUNCTIONS		are in Inches
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at <u>www.rtautomation.com/products</u> . We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION					
460MCTCP-NNA1		Connects up to 32 Modbus TCP servers with as many as 10 Ethernet TCP/IP devices				
Ĕ		Row	WARRANTY	İİ		
ALWAYS IN STOCK	READY TO SHIP	ENGINERD SUPPORT	5-YEAR WARRANTY	EMPLOYEE OWNED		

Real Time Automation, Inc.

solutions@rtautomation.com