460MMBC-N34

Modbus RTU Servers to BACnet/IP

FEATURES

- Fully configurable Modbus RTU Client
- Connects up to 32
 Modbus RTU Servers
- Fully configurable BACnet/IP client
- BACnet/IP supports device, binary I/O/V, analog I/O/V, multistate I/O/V, and character string value object types
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect Modbus RTU Servers to BACnet/IP Server Devices

The 460MMBM moves data between a network of up to 32 Modbus RTU Servers and up to 32 BACnet/IP devices.

With the 460MMBM, you're mapping Modbus coil and register data directly to BACnet/IP as binary and analog values.

How Do I Use the 460MMBC-N34 in My Application?

Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to Binary objects. The only additional piece required for BACnet is adding metadata which is nothing more than an ASCII description of each object. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

MODBUS RTU CLIENT FEATURES		
Operation Mode	Modbus RTU Client	
Function Codes Supported	1,2,3,4,5,6, 15 & 16	
Swapping	Byte and Word Swapping	
Maximum Modbus RTU Server Devices	32	
Number Read/Write Scan Lines per RTU Server Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 125 Registers or 512 Coils	
BACNET IP CLIENT FEATURES		
Operation Mode	BACnet/IP Client	
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value	
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A	
Maximum Connections	32	
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 128 Objects	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

8 VDC @ 230mA to 28 VDC @ 80 mA 115K baud -40 C to 85 C	LED		
-40 C to 85 C	reo		
	, ,		
Dallo Carrallant III Oll OF Arranavala Olasa			
RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	[[Pod 0000
ENCLOSURE / HARDWARE			
4.2" x 3.25" x 1"	3.25		
7 oz			Port 0
Anodized Aluminum			000000
Din rail or panel mount			
	1.00	4.19	1.00
GATEWAY FEATURES & FUNCTIONS			
Set <, <=, >, >=, ==, !=, and change-of-state rules on	On item	_	-
any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Panel Mount	<u> </u>	_
You can configure up to 9 different users access to diagnostic and configuration screens.			
Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.			
Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications.		
Allows users to see and log start up sequences, protocol specific messages & error messages.			
	4.2" x 3.25" x 1" 7 oz Anodized Aluminum Din rail or panel mount Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. Allows users to see and log start up sequences,	4.2" x 3.25" x 1" 7 oz Anodized Aluminum Din rail or panel mount Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. Allows users to see and log start up sequences,	4.2" x 3.25" x 1" 7 oz Anodized Aluminum Din rail or panel mount Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. Allows users to see and log start up sequences, Allows users to see and log start up sequences,

	CATALOG #	DESCRIPTION
	460MMBC-N34	Connects up to 32 Modbus RTU Servers with as many as 32 BACnet /IP Servers









