### **460MMDFM-N34**

### **Connect Modbus RTU Servers to Legacy Serial DF1 PLCs**

## **FEATURES**

- Fully configurable Modbus RTU Client
- Connects up to 32
  Modbus RTU Servers
- Support for PLC5, SLC and MicroLogix PLCs
- Connect up to 32 DF1 serial devices
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

# Connect Up To 32 Modbus RTU Server Devices to a Serial PLC5, SLC or MicroLogix PLC

You can now connect a network of up to 32 Modbus RTU Servers to a legacy Allen-Bradley PLC over DF1.

It's the perfect tool to save legacy PLCs from the scrap pile and extend their useful life.

#### How Do I Use the 460MMDFM-N34 in My Application?

The mapping is very straightforward. Modbus register and coil data is mapped to files in the PLCs data tables. For example, you can map N7:200 to Modbus register 40200 in Modbus server 10. Data transfer is bidirectional. It really is that simple.

### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.







RTU Servers

460MMDFM-N34

**DF1 Slave Devices** 

A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

## **Specification**

MODBUS RTU CLIENT FEATURES		
Operation Mode	Modbus RTU Client	
Function Codes Supported	1,2,3,4,5,6, 15 & 16	
Swapping	Byte and Word Swapping	
Maximum Modbus RTU Server Devices	32	
Number Read/Write Scan Lines per RTU Server Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 125 Registers or 512 Coils	
DF1 MASTER FEATURES		
Operation Mode	DF1 Master Full Duplex and DF1 Master Half Duplex	
PLCs Supported	MicroLogix 1000, SLC 5/03 5/04 5/05, most PLC5s	
Maximum number of Devices supported	1 in Full Duplex Mode, 32 in Half Duplex	
Data Type Supported	100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line	
Scan Lines	100 input / 100 output	
Physical Connections	RS-485 and RS-232	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Optional: Generic 1761-CBL-PM02 Cable	Optional: NULL Modem Cable	

ELECTRICAL / ENVIRONMENTAL			
DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA		
Maximum Baud Rate	115K baud	LEOS	
Operating Temperature	-40 C to 85 C		
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2		Pod 00000
ENCLOSURE / HARDWARE		3,25	
Size	4.2" x 3.25" x 1"	3.25	
Weight	7 oz		
Enclosure Type	Anodized Aluminum		Perto
Mounting	Din rail or panel mount		
LEDs	Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side	1.00 4.19	1.00
GATEWAY FEATURES & FUNCTIONS		Din Rail	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Panel Mount	<u>-</u> =
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	••••	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.		
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WE Real Time Automation offers a full lir Give us a call at 1-800-249-1612. C www.rtautomation.com/produ customizations for unique	ne of gateway products. Or, check out a listing at octs. We also offer
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.		

	CATALOG #	DESCRIPTION
	460MMDFM-N34	Connects up to 32 Modbus RTU Servers with as many as 32 DF1 slaves









