## **460MMQT-N2E**

### **Modbus RTU Server to MQTT Broker**

## **FEATURES**

- Fully configurable Modbus RTU Client
- Connects up to 32
   Modbus RTU Servers
- Bring your factory data to the cloud
- Supports up to 3 MQTT broker connections
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

# Bridge up to 31 Modbus RTU Server Devices to an MQTT Broker

The 460MMQT moves data between up to 32 Modbus RTU Server devices and an MQTT platform. Allowing you to easily log data and leverage in populating dashboards.

Best of all, the product comes with 5-year warranty.

#### How Do I Use the 460MMQT-N2E in My Application?

Modbus register and coil data is mapped to and from topics in an MQTT broker. SSL transport layer security protects the data moving from your operations network to the cloud.

### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

MODBUS RTU CLIENT FEATURES	
Operation Mode	Modbus RTU Client
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus RTU Server Devices	32
Number Read/Write Scan Lines per RTU Server Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 125 Registers or 512 Coils
MQTT CLIENT FEATURES	
Operation Mode	Generic MQTT, Amazon Web Services (AWS)
Max Broker Connections	Up to 3 Generic MQTT Connections or 1 AWS
Max Data Points Per Connection	250 Read Topics, 250 Write Topics
Security	SSL certificate based cloud access
Supported Data Formats	JSON
Data Payload	Topic Name and Value
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

Status and Counters  Status and Counters  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a	ELECTRICAL / ENVIRONMENTAL		
Operating Temperature  -40 C to 85 C  Certification  RoHS-Compliant, UL, CUL, CE Approvals, Class 1 Div 2  ENCLOSURE / HARDWARE Size  5.40" x 3.83" x 1.19"  Weight  7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount LEDs Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS  Set <, <, >, >, =, =, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offe customizations for unique applications.	DC Input Voltage	12-24 VDC	
Certification  RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2  ENCLOSURE / HARDWARE  Size  5.40" x 3.83" x 1.19"  Weight  7.6 oz  Enclosure Type  Anodized Aluminum  Mounting  Din rail or panel mount  LEDs  Power LED & 2 general purpose LEDs on side  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, =, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.	Maximum Baud Rate	115K baud	<b>□ (• • •</b>
ENCLOSURE / HARDWARE  Size  5.40" x 3.83" x 1.19"  Weight  7.6 oz  Enclosure Type  Anodized Aluminum  Mounting  Din rail or panel mount  LEDs  Power LED & 2 general purpose LEDs on side  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	Operating Temperature	-40 C to 85 C	
Size    5.40" x 3.83" x 1.19"   Weight   7.6 oz     Enclosure Type   Anodized Aluminum     Mounting   Din rail or panel mount     LEDs   Power LED & 2 general purpose LEDs on side     GATEWAY FEATURES & FUNCTIONS     Alarming   Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.     You can configure up to 9 different users access to diagnostic and configuration screens.     Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.     Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.     NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list     Www.rtautomation.com/products. We also offer customizations for unique applications.	Certification		3.83
Size  S.40 X 3.83 X 1.19  Weight  7.6 oz  Anodized Aluminum  Mounting  LEDs  Power LED & 2 general purpose LEDs on side  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	ENCLOSURE / HARDWARE		0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Weight 7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount LEDs Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	Size	5.40" x 3.83" x 1.19"	
Mounting  Din rail or panel mount Power LED & 2 general purpose LEDs on side  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	Weight	7.6 oz	
Power LED & 2 general purpose LEDs on side  GATEWAY FEATURES & FUNCTIONS  Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  Allows users to see and log start up sequences,  Allows users to see and log start up sequences,	Enclosure Type	Anodized Aluminum	
Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profix give us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	Mounting	Din rail or panel mount	
Alarming any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	LEDs	Power LED & 2 general purpose LEDs on side	
Alarming any data moving through the gateway. If alarm rule is triggered an email notification can be sent.  You can configure up to 9 different users access to diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	GATEWAY FEATURES & FUNCTIONS		
diagnostic and configuration screens.  Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	Alarming	any data moving through the gateway. If alarm rule	
Translation Table  translation. Scaling and other data format changes can occur in the gateway.  Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profers us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	Gateway Security		
Status and Counters  Real Time Automation offers a full line of gateway program as a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.  Allows users to see and log start up sequences,	Translation Table	translation. Scaling and other data format changes	
Disanctic Logging Dage	Status and Counters	messages are accessible within the gateway's diagnostics page. They can also be delivered to a	NOT EXACTLY WHAT YOU WERE LOOKING FOR?  Real Time Automation offers a full line of gateway products.  Give us a call at 1-800-249-1612. Or, check out a listing at <a href="https://www.rtautomation.com/products">www.rtautomation.com/products</a> . We also offer customizations for unique applications.
	Diagnostic Logging Page		

CATALOG #	DESCRIPTION
460MMQT-N2E	Easily and securely connect Modbus RTU devices to an MQTT broker









