460MMSC-NNA4

Modbus RTU to Siemens S7 PLC

FEATURES

- Fully configurable Modbus RTU Client
- Connects up to 32
 Modbus RTU Servers
- Supports connections to five Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Get Your Modbus RTU Server Devices Connected Directly to the Data Table of Your Siemens S7 PLC

The 460MMSC connects 32 Modbus RTU Server devices with up to five Siemens S7 PLCs.

Best of all, the product comes with 5-year warranty.


How Do I Use the 460MMSC-NNA4 in My Application?

You allocate two memory blocks in your Siemens S7 PLC. One area is a user-defined set of output addresses sending data to your Modbus RTU Servers. The other is input only data receiving data from your Modbus RTU Servers. It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

| MODBUS RTU CLIENT FEATURES | |
|---|--|
| Operation Mode | Modbus RTU Client |
| Function Codes Supported | 1,2,3,4,5,6, 15 & 16 |
| Swapping | Byte and Word Swapping |
| Maximum Modbus RTU Server Devices | 32 |
| Number Read/Write Scan Lines per RTU Server Device | 200 Total - 100 reads & 100 writes |
| Scan Line Support | Up to 125 Registers or 512 Coils |
| Siemens S7 CLIENT FEATURES | |
| PLC Support | S7 300/400/1200/1500 |
| Maximum Number of PLCs Supported | 5 |
| Maximum Number of Inputs/Outputs per PLC | 150 |
| Maximum Number of Bytes per Scan Line | 400 |
| Memory Area Access | Input (I), Output (Q), and Data Block(DB) |
| Supported Data Types | 8 Bit Int, 16 Bit Int, 32 Bit Int, 32 Bit Float, Bool and Char Array |
| INCLUDED WITH GATEWAY | |
| 3' power cable with flying leads | 5-year hardware warranty |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff |
| Manual | |

| ELECTRICAL / ENVIRONMENT | AL | |
|---------------------------------|---|---|
| DC Input Voltage | 12-24 VDC | |
| Maximum Baud Rate | 115K baud | DIN Rail Mount |
| Operating Temperature | -40 C to 85 C | |
| Certification | RoHS-Compliant, UL, CUL, CE Approvals | , |
| ENCLOSURE / HARDWARE | | |
| Size | 3.88" x 2.57" x 1.06" | |
| Weight | 5.5 oz | |
| Enclosure Type | Anodized Aluminum | 2.57 |
| Mounting | Din rail or panel mount | |
| LEDs | Power LED & 2 general purpose LEDs on side | Note: All dimensions |
| GATEWAY FEATURES & FUNCTIONS | | are in Inches |
| Alarming | Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. | 99999 99 |
| Gateway Security | You can configure up to 9 different users access to diagnostic and configuration screens. | |
| Translation Table | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. | |
| Status and Counters | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. | NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications. |
| Diagnostic Logging Page | Allows users to see and log start up sequences, protocol specific messages & error messages. | |

| CATALOG # | DESCRIPTION |
|--------------|---|
| 460MMSC-NNA4 | Connects up to five Siemens S7 PLCs with as many as 32 Modbus RTU Servers |









