460MRSBM-N700

Modbus RTU to BACnet MS/TP Device

FEATURES

- Fully configurable Modbus RTU Server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus RTU Client
- Fully configurable BACnet MS/TP Manager
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect BACnet MS/TP Devices to a Modbus RTU Client

The 460MRSBM moves data between a Modbus RTU Client device and up to 32 BACnet MS/TP devices.

With the 460MRSBM, you're mapping BACnet MS/TP as binary and analog values directly to your Modbus RTU Client.

How Do I Use the 460MRSBM-N700 in My Application?

Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to binary objects on BACnet. The only additional piece required for BACnet is adding metadata which is nothing more than an ASCII description of each object. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.









RTU Clients

460MRSBM-N700

MS/TP Subordinates

A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

Operation Mode	Modbus RTU Server	
Function Codes Supported	1,2,3,4,5,6, 15 & 16	
Swapping	Byte and Word Swapping	
Maximum Modbus RTU Client Connections	1	
Contiguous Data Areas	200 Total - 100 reads & 100 writes	
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers	
BACNET MS/TP MANAGER FEATURES		
Operation Mode	BACnet MS/TP Manager Initiator	
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value	
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A	
Maximum Connections	32	
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 128 Objects	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	Ithernet
ENCLOSURE / HARDWARE	110.10 00mpnam, 02, 002, 02 rpp.ora.o	Ithernet 6
Size	4.19" x 3.25" x 1"	3,26
Weight	6.5 oz	
Enclosure Type	Anodized Aluminum	Note: All dimension are in notes
Mounting	Din rail or panel mount	are n inches
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	-1.00
GATEWAY FEATURES & FUNCTIONS		01.0.1
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Din Rail Panel Mount
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	• • •
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460MRSBM-N700	Connects a Modbus RTU Client with as many as 32 BACnet MS/TP Subordinates









