460MRSQT-N2E

Modbus RTU Client to MQTT Broker

FEATURES

- Fully configurable Modbus RTU Server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus RTU Client
- Bring your factory data to the cloud
- Supports up to 3 MQTT broker connections
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect a Modbus RTU Client to a Cloud-Based Application via MQTT

The 460MRSQT moves data between a Modbus RTU Server device and an MQTT platform. Allowing you to easily log data and leverage in populating dashboards. Best of all, the product comes with 5-year warranty.

How Do I Use the 460MRSQT-N2E in My Application?

Modbus register and coil data is mapped to and from topics in an MQTT broker. SSL transport layer security protects the data moving from your operations network to the cloud.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

| MODBUS RTU SERVER FEATURES | |
|---|--|
| Operation Mode | Modbus RTU Server |
| Function Codes Supported | 1,2,3,4,5,6, 15 & 16 |
| Swapping | Byte and Word Swapping |
| Maximum Modbus RTU Client Connections | 1 |
| Contiguous Data Areas | 200 Total - 100 reads & 100 writes |
| Data Area Limits | 512 Contiguous Coils or 512 Contiguous Registers |
| MQTT CLIENT FEATURES | |
| Operation Mode | Generic MQTT, Amazon Web Services (AWS) |
| Max Broker Connections | Up to 3 Generic MQTT Connections or 1 AWS |
| Max Data Points Per Connection | 250 Read Topics, 250 Write Topics |
| Security | SSL certificate based cloud access |
| Supported Data Formats | JSON |
| Data Payload | Topic Name and Value |
| INCLUDED WITH GATEWAY | |
| 3' power cable with flying leads | 5-year hardware warranty |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff |
| Manual | |

| ELECTRICAL / ENVIRONMENTAL | | |
|------------------------------|---|--|
| DC Input Voltage | 12-24 VDC | |
| Maximum Baud Rate | 115K baud | □ (6 □0) |
| Operating Temperature | -40 C to 85 C | |
| Certification | RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2 | 3.83 |
| ENCLOSURE / HARDWARE | | 0 0 1 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 |
| Size | 5.40" x 3.83" x 1.19" | |
| Weight | 7.6 oz | |
| Enclosure Type | Anodized Aluminum | |
| Mounting | Din rail or panel mount | |
| LEDs | Power LED & 2 general purpose LEDs on side | |
| GATEWAY FEATURES & FUNCTIONS | | |
| Alarming | Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. | |
| Gateway Security | You can configure up to 9 different users access to diagnostic and configuration screens. | |
| Translation Table | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. | |
| Status and Counters | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. | NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications. |
| Diagnostic Logging Page | Allows users to see and log start up sequences, protocol specific messages & error messages. | |

| CATALOG # | DESCRIPTION |
|--------------|--|
| 460MRSQT-N2E | Easily and securely connect a Modbus RTU Client device to an MOTT broker |









