460MRSSC-N700

Siemens S7 PLC to Modbus Client

FEATURES

- Fully configurable Modbus RTU Server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus RTU Client
- Supports connections to five Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Get Your Modbus RTU Client Connected Directly to the Data Table of Your Siemens S7 PLC over Wi-Fi

The 460MRSSC connects a Modbus RTU Client device with up to five Siemens S7 PLCs.

Best of all, the product comes with 5-year warranty.

How Do I Use the 460MRSSC-N700 in My Application?

You allocate two memory blocks in your Siemens S7 PLC. One area is a user-defined set of output addresses sending data to your Modbus RTU Client. The other is input only data receiving data from your Modbus RTU Client.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

Operation Mode	Modbus RTU Server
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus RTU Client Connections	1
Contiguous Data Areas	200 Total - 100 reads & 100 writes
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers
Siemens S7 CLIENT FEATURES	
PLC Support	S7 300/400/1200/1500
Maximum Number of PLCs Supported	5
Maximum Number of Inputs/Outputs per PLC	150
Maximum Number of Bytes per Scan Line	400
Memory Area Access	Input (I), Output (Q), and Data Block(DB)
Supported Data Types	8 Bit Int, 16 Bit Int, 32 Bit Int, 32 Bit Float, Bool and Char Array
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	Imerinet
ENCLOSURE / HARDWARE		87
Size	4.19" x 3.25" x 1"	3.26
Weight	6.5 oz	
Enclosure Type	Anodized Aluminum	Note: All dimension are n inches
Mounting	Din rail or panel mount	are n inches
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	-1.00
GATEWAY FEATURES & FUNCTION	ONS	Die Deit
	Set <, <=, >, >=, ==, !=, and change-of-state rules on	Din Rail
Alarming	any data moving through the gateway. If alarm rule	
Ü	is triggered an email notification can be sent.	Panel Mount
Gateway Security	You can configure up to 9 different users access to	Panel Mount
	diagnostic and configuration screens.	
	Allows for data manipulation during protocol	
Translation Table	translation. Scaling and other data format changes	
	can occur in the gateway.	
	Protocol specific status, counters, and error	NOT EXACTLY WHAT YOU WERE LOOKING FOR?
	messages are accessible within the gateway's	Real Time Automation offers a full line of gateway products
Status and Counters	diagnostics page. They can also be delivered to a	Give us a call at 1-800-249-1612. Or, check out a listing at
	connected device.	www.rtautomation.com/products. We also offer
	connected device.	customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences,	
20	protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460MRSSC-N700	Connects up to five Siemens S7 PLCs with a Modbus RTU Client









