460MSBC-N700

BACnet/IP to Modbus TCP/IP Client

FEATURES

- Fully configurable Modbus TCP/IP server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus TCP/IP client
- Fully configurable BACnet/IP client
- BACnet/IP supports device, binary I/O/V, analog I/O/V, multistate I/O/V, and character string value object types
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect BACnet/IP Server Devices to a Modbus TCP/IP Client

The 460MSBC moves data between a network of up to 32 BACnet/IP server devices and a Modbus TCP/IP client.

It's a perfect tool to get your Modbus TCP/IP data tied in with your BACnet/IP devices. Featuring separate Ethernet network connections for your Modbus TCP/IP and building automation network.

How Do I Use the 460MSBC-N700 in My Application?

Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to binary objects on BACnet. The final step to add meaning names to each BACnet object for easy discovery in the BMS. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

Operation Mode	Modbus TCP/IP Server		
Function Codes Supported	1,2,3,4,5,6, 15 & 16		
Swapping	Byte and Word Swapping		
Maximum Modbus TCP/IP Client Connections	10		
Contiguous Data Areas	200 Total - 100 reads & 100 writes		
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers		
BACNET IP CLIENT FEATURES			
Operation Mode	BACnet/IP Client		
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value		
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A		
Maximum Connections	32		
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes		
Scan Line Support	Up to 128 Objects		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
Manual			

LECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	Ithernet 5
ENCLOSURE / HARDWARE		
Size	4.19" x 3.25" x 1"	3.26
Weight	6.5 oz	li l
Enclosure Type	Anodized Aluminum	Note: Al dimension are numbers
Mounting	Din rail or panel mount	are n inches
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	-1.001.00
GATEWAY FEATURES & FUNCTIONS		Din Rail
	Set <, <=, >, >=, ==, !=, and change-of-state rules on	Uin Rail
Alarming	any data moving through the gateway. If alarm rule	
<u> </u>	is triggered an email notification can be sent.	Panel Mount
Gateway Security	You can configure up to 9 different users access to	Pariet Modrit
	diagnostic and configuration screens.	
	Allows for data manipulation during protocol	
Translation Table	translation. Scaling and other data format changes	
	can occur in the gateway.	
	Dust and amonific status countains and amon	NOT EXACTLY WHAT YOU WERE LOOKING FOR?
Status and Counters	Protocol specific status, counters, and error	Real Time Automation offers a full line of gateway products.
	messages are accessible within the gateway's	Give us a call at 1-800-249-1612. Or, check out a listing at
	diagnostics page. They can also be delivered to a connected device.	www.rtautomation.com/products. We also offer
	connected device.	customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences,	
Diagnostic Logging Lage	protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460MSBC-N700	Connects a Modbus TCP client with as many as 32 BACnet/IP servers









