

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460MSBC-NNA4

BACnet/IP to Modbus TCP/IP Client

FEATURES

- Fully configurable Modbus TCP/IP server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus TCP/IP client
- Fully configurable BACnet/IP client
- BACnet/IP supports device, binary I/O/V, analog I/O/V, multistate I/O/V, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect BACnet/IP Server Devices to a Modbus TCP/IP Client

The 460MSBC moves data between a network of up to 32 BACnet/IP server devices and a Modbus TCP/IP Client. Featuring separate Ethernet network connections for your Modbus TCP/IP and building automation network.

It's a perfect tool to get your Modbus TCP/IP data tied in with your BACnet/IP devices. Featuring separate Ethernet network connections for your Modbus TCP/IP and building automation network.

How Do I Use the 460MSBC-NNA4 in My Application?

Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to binary objects on BACnet. The final step to add meaning names to each BACnet object for easy discovery in the BMS. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

MODBUS TCP SERVER FEATURES				
Operation Mode	Modbus TCP/IP Server			
Function Codes Supported	1,2,3,4,5,6, 15 & 16			
Swapping	Byte and Word Swapping			
Maximum Modbus TCP/IP Client Connections	10			
Contiguous Data Areas	200 Total - 100 reads & 100 writes			
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers			
BACNET IP CLIENT FEATURES				
Operation Mode	BACnet/IP Client			
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value			
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A			
Maximum Connections	32			
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes			
Scan Line Support	Up to 128 Objects			
INCLUDED WITH GATEWAY				
3' power cable with flying leads	5-year hardware warranty			
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life			
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff			
Manual				

ELECTRICAL / ENVIRONMENTAL					
DC Input Voltage	12-24 VDC				
Maximum Baud Rate 115K baud		DIN Rail Mount			
Operating Temperature	-40 C to 85 C		3.88		
Certification	RoHS-Compliant, UL, CUL, CE Approvals)		
ENCLOSURE / HARDWARE					
Size	3.88" x 2.57" x 1.06"				
Weight	5.5 oz				
Enclosure Type	Anodized Aluminum	2.57			
Mounting	Din rail or panel mount				
LEDs	Power LED & 2 general purpose LEDs on side		Note: All dimensions		
GATEWAY FEATURES & FUNCTIONS			are in Inches		
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	·	69869 69		
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	1.06			
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.				
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	Real Time Au Give us a cal <u>www.rt</u>	CTLY WHAT YOU WERE LOOKING FOR? tomation offers a full line of gateway products. I at 1-800-249-1612. Or, check out a listing at tautomation.com/products. We also offer stomizations for unique applications.		
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.				

CATALOG #	DESCRIPTION					
460MSBC-NNA4	Connects a Modbus TCP client with as many as 32 BACnet/IP servers					
~		6	Participant and a second se			
Ä		Row	WARRANTY	ĬĨ		
ALWAYS IN STOCK	READY TO SHIP	ENGINERD SUPPORT	5-YEAR WARRANTY	EMPLOYEE OWN		

Real Time Automation, Inc.

solutions@rtautomation.com