

CONTACT US! 1-800-249-1612 rtautomation.com

460MSBM-NNA1

BACnet MS/TP to Modbus TCP/IP Client

FEATURES

- Fully configurable Modbus TCP/IP server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus TCP/IP client
- Fully configurable BACnet MS/TP Manager
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect BACnet MS/TP Devices to a Modbus TCP/IP Client

The 460MSBM moves data between a network of up to 32 BACnet MS/TP devices and a Modbus TCP/IP client.

It's a perfect tool to get your Modbus TCP/IP data tied in with your BACnet MS/TP devices.

How Do I Use the 460MSBM-NNA1 in My Application?

Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to binary objects on BACnet. The final step to add meaning names to each BACnet object for easy discovery in the BMS. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



TCP/IP Client







460MSBM-NNA1

MS/TP Subordinates

A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

11-1-6

Specification

MODBUS TCP SERVER FEATURES	
Operation Mode	Modbus TCP/IP Server
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus TCP/IP Client Connections	10
Contiguous Data Areas	200 Total - 100 reads & 100 writes
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers
BACNET MS/TP MANAGER FEATURES	
Operation Mode	BACnet MS/TP Manager Initiator
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A
Maximum Connections	32
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 128 Objects
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

ELECTRICAL / ENVIRONMENTAL			
DC Input Voltage	12-24 VDC		
Maximum Baud Rate	115K baud	DIN Rail Mount	
Operating Temperature	-40 C to 85 C	3.88	
Certification	RoHS-Compliant, UL, CUL, CE Approvals		
ENCLOSURE / HARDWARE			
Size	3.88" x 2.57" x 1.06"		
Weight	5.5 oz		
Enclosure Type	Anodized Aluminum	2.57	
Mounting	Din rail or panel mount		
LEDs	Power LED & 2 general purpose LEDs on side	Note: All dimensions	
GATEWAY FEATURES & FUNCTIONS		are in Inches	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.		
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.		
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.		
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.	
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.		

CATALOG #	DESCRIPTION				
460MSBM-NNA1	Connects a Modbus TCP client with as many as 32 BACnet MS/TP Subordinates				
	– –		TARRANTY		
	<u>6</u> 0	COO	A A A A A A A A A A A A A A A A A A A		

READY TO SHIP

Real Time Automation, Inc.

ALWAYS IN STOCK

solutions@rtautomation.com

5-YEAR WARRANTY

ENGINERD SUPPORT

EMPLOYEE OWNED