

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460MSBS-N2E

Modbus TCP/IP Client to BACnet/IP

FEATURES

- Fully configurable Modbus TCP/IP server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus TCP/IP client
- Fully configurable BACnet/IP server
- BACnet/IP supports device, binary I/O, analog I/O, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect a Modbus TCP/IP Client to a BACnet/IP Client

The 460MSBS moves data between a Modbus TCP/IP client and a BACnet/IP Building Automation System (BAS). It's a perfect way to implement legacy and also new, cost-effective Modbus TCP/IP controller into your BACnet/IP architecture. Best of all, the product comes with 5-year warranty.

How Do I Use the 460MSBS-N2E in My Application?

Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to binary objects on BACnet. The final step to add meaning names to each BACnet object for easy discovery in the BMS.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

MODBUS TCP SERVER FEATURES		
Operation Mode	Modbus TCP/IP Server	
Function Codes Supported	1,2,3,4,5,6, 15 & 16	
Swapping	Byte and Word Swapping	
Maximum Modbus TCP/IP Client Connections	10	
Contiguous Data Areas	200 Total - 100 reads & 100 writes	
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers	
BACNET IP SERVER FEATURES		
Operation Mode	BACnet/IP Server	
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value	
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B	
Maximum COV Subscriptions	2800	
Analog Objects Supported	1200 Input and 1200 Output	
Binary Objects Supported	1600 Input and 1600 Output	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENTAL	_	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	3.83 - 1.19
ENCLOSURE / HARDWARE		0 0 0
Size	5.40" x 3.83" x 1.19"	
Weight	7.6 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	
GATEWAY FEATURES & FUNCTIONS		
	Set <, <=, >, >=, ==, !=, and change-of-state rules on	
Alarming	any data moving through the gateway. If alarm rule	
-	is triggered an email notification can be sent.	
Gateway Security	You can configure up to 9 different users access to	
	diagnostic and configuration screens.	
	Allows for data manipulation during protocol	
Translation Table	translation. Scaling and other data format changes	
	can occur in the gateway.	
	3 ,	NOT EXACTLY WHAT YOU WERE LOOKING FOR?
	Protocol specific status, counters, and error	Real Time Automation offers a full line of gateway products.
Status and Counters	messages are accessible within the gateway's	Give us a call at 1-800-249-1612. Or, check out a listing at
Status and Counters	diagnostics page. They can also be delivered to a	www.rtautomation.com/products. We also offer
	connected device.	customizations for unique applications.
	Allows users to see and log start up sequences,	
Diagnostic Logging Page	protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460MSBS-N2E	Connects a Modbus TCP client with a BACnet/IP client







5-YEAR WARRANTY



solutions@rtautomation.com