

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460PSBM-N700

BACnet MS/TP Devices to PROFINET IO

FEATURES

- Fully configurable PROFINET device
- Supports up to 1280 bytes of data in each direction on PROFINET IO
- Fully configurable
 BACnet MS/TP
 Manager
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Get Your BACnet MS/TP Devices Connected to a PROFINET IO Controller

The 460PSBM moves data between a network of up to 32 BACnet MS/TP devices and a PROFINET IO controller.

Best of all, the product comes with 5-year warranty.

How Do I Use the 460PSBM-N700 in My Application?

BACnet MS/TP data will be mapped into 10 PROFINET IO slots. Each Slot will be assigned a data type and consist of up to 128 bytes of data. This data will be mapped to and from BACnet MS/TP analog and binary values.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

PROFINET SERVER FEATURES		
Maximum Number of Slots	10 Slots in, 10 Slots out	
Slot Data Segment Sizes	8, 16, 32, 64 or 128 Bytes	
Each Slot Can be Defined for a Single Data Type of	Int8, int16, int32, int64, UInt8, Uint16, Uint32, Uint64, float, double, binary8, binary16 or binary32, Short String	
Total Data Supported in Each Direction	1280 Bytes	
Maximum Profinet IO Controller Connections	1	
String Support	1 string per slot	
BACNET MS/TP MANAGER FEATURES		
Operation Mode	BACnet MS/TP Manager Initiator	
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value	
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A	
Maximum Connections	32	
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 128 Objects	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENTAL

LEECTRICKE/ ENVIRONMENT/	1	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	- 6
Certification	RoHS-Compliant, UL, CUL, CE Approvals	Ethernet de constant
ENCLOSURE / HARDWARE		E S
Size	4.19" x 3.25" x 1"	3,25
Weight	6.5 oz	
Enclosure Type	Anodized Aluminum	Note: Al dimension
Mounting	Din rail or panel mount	are ninches
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	·
GATEWAY FEATURES & FUNC	TIONS	Din Rail
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Panel Mount
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	• • • •
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at <u>www.rtautomation.com/products</u> . We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460PSBM-N700	Connects a PROFINET IO controller with up to 32 BACnet MS/TP Subordinates





WARRAN

T 5-YEAR WARRANTY

solutions@rtautomation.com



1-800-249-1612

Real Time Automation, Inc.