

CONTACT US! 1-800-249-1612 rtautomation.com

460PSBMS-N2E

PROFINET IO to BACnet MS/TP Manager

FEATURES

- Fully configurable PROFINET device
- Supports up to 1280 bytes of data in each direction on PROFINET IO
- Fully configurable BACnet MS/TP Subordinate
- BACnet MS/TP supports device, binary I/O, analog I/O, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Get Your PROFINET IO Controller Connected to a BACnet MS/TP Manager

The 460PSBMS moves data between a PROFINET IO controller and a BACnet MS/TP Manager.

With the 460PSBMS, you are making a direct connection between PROFINET IO data and your BACnet MS/TP building automation system.

How Do I Use the 460PSBMS-N2E in My Application?

BACnet MS/TP Manager data will be mapped into 10 PROFINET IO slots. Each slot will be assigned a data type and consist of up to 128 bytes of data. This data will be mapped to and from BACnet analog and binary objects.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

PROFINET SERVER FEATURES			
Maximum Number of Slots	10 Slots in, 10 Slots out		
Slot Data Segment Sizes	8, 16, 32, 64 or 128 Bytes		
Each Slot Can be Defined for a Single Data Type of	Int8, int16, int32, int64, UInt8, Uint16, Uint32, Uint64, float, double, binary8, binary16 or binary32, Short String		
Total Data Supported in Each Direction	1280 Bytes		
Maximum Profinet IO Controller Connections	1		
String Support	1 string per slot		
BACNET MS/TP RESPONDER FEATURES			
Operation Mode	BACnet MS/TP Manager Responder		
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value		
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B		
Maximum Connections	1		
Analog Objects Supported	1200 Input and 1200 Output		
Binary Objects Supported	1600 Input and 1600 Output		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
Manual			

ELECTRICAL / ENVIRONMENTAL

ELECTRICAL / ENVIRONMENT	AL	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	3.83 - 1.19 -
ENCLOSURE / HARDWARE		
Size	5.40" x 3.83" x 1.19"	
Weight	7.6 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	
GATEWAY FEATURES & FUNC	TIONS	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway product: Give us a call at 1-800-249-1612. Or, check out a listing a <u>www.rtautomation.com/products</u> . We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460PSBMS-N2E	Connects a PROFINET IO controller with a BACnet MS/TP Manager







ENGINERD SUPPORT

5-YEAR WARRANTY

solutions@rtautomation.com



1-800-249-1612

Real Time Automation, Inc.