## 460TCPSC-NNA1

### **TCP/IP Socket Connection to Siemens S7 PLCs**

## **FEATURES**

- Support up to 10 TCP/IP devices
- Parse & concatenate ASCII/HEX data in up to 50 segments by delimiter or offset
- Supports connections to five Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

#### Map Your Siemens S7 PLC Data to a TCP/IP Socket

The 460TCPSC moves data between up to 10 Ethernet TCP/IP devices and up to five Siemens S7 PLCs.

Best of all, the product comes with 5-year warranty.

#### How Do I Use the 460TCPSC-NNA1 in My Application?

Incoming and outgoing ASCII data in TCP/IP packets are parsed into data segments and given a data type. Those values are them mapped to mating memory locations in your Siemens S7 PLC.

It really is that simple.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

# **Specification**

ETHERNET TCP/IP FEATURES	
Operation Mode	Client or Server
Maximum Number of Devices Supported	10
Maximum Number of Characters Transferred	1024
Delimiter Processing	Incoming delimiters can be automatically removed; Outgoing delimiters automatically added if configured
Parsing	Parse String of ASCII Data in up to 50 Segments by Delimiter or Offset
Concatenation	Concatenate up to 50 segments/strings of ASCII data with optional delimiter
Siemens S7 CLIENT FEATURES	
PLC Support	S7 300/400/1200/1500
Maximum Number of PLCs Supported	5
Maximum Number of Inputs/Outputs per PLC	150
Maximum Number of Bytes per Scan Line	400
Memory Area Access	Input (I), Output (Q), and Data Block( DB)
Supported Data Types	8 Bit Int, 16 Bit Int, 32 Bit Int, 32 Bit Float, Bool and Char Array
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

ELECTRICAL / ENVIRONMENTA	<b>\</b> L	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	DIN Rail Mount
Operating Temperature	-40 C to 85 C	3.88 —
Certification	RoHS-Compliant, UL, CUL, CE Approvals	,
ENCLOSURE / HARDWARE		
Size	3.88" x 2.57" x 1.06"	
Weight	5.5 oz	
Enclosure Type	Anodized Aluminum	2.57
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	Note: All dimensions
GATEWAY FEATURES & FUNCTIONS		are in Inches
	Set <, <=, >, >=, ==, !=, and change-of-state rules on	·
Alarming	any data moving through the gateway. If alarm rule	0000 00
C	is triggered an email notification can be sent.	
Gateway Security	You can configure up to 9 different users access to	
	diagnostic and configuration screens.	
	Allows for data manipulation during protocol	
Translation Table	translation. Scaling and other data format changes	
	can occur in the gateway.	
	Protocol specific status, counters, and error	NOT EXACTLY WHAT YOU WERE LOOKING FOR?
Status and Counters	messages are accessible within the gateway's	Real Time Automation offers a full line of gateway products.
	diagnostics page. They can also be delivered to a	Give us a call at 1-800-249-1612. Or, check out a listing at
	connected device.	www.rtautomation.com/products. We also offer
	connected device.	customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences,	
2.50.100.50 2000116 1 460	protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460TCPSC-NNA1	Connects up to 10 Ethernet TCP/IP devices with as many as five Siemens S7 PLCs









