

### Contact Us! 1-800-249-1612 www.rtautomation.com

## **Real Time Automation Gateways**

## 460WISC-N34

## Web Interface for Siemens S7 PLCs

# **FEATURES**

- Get PLC data table entries encoded in either JSON or XML
- Bidirectional Data Transfer supports both HTTP GET and POST
- Supports connections to 5 Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

#### Access your Siemens S7 PLC Data via a Web Interface

The 460WISC moves data between up to five Siemens S7 PLCs via Web Services. Access data via HTTP calls.

With the 460WISC you are making a direct connection between XML/JSON data and data table of your Siemens S7 PLC.



#### How do I use 460WISC-N34 in my application?

Incoming and outgoing ASCII data is mapped to and from memory table addresses in your Siemens S7 PLC. One area is Output being mapped as XML or JSON to your applications. The other is Input blocks receiving data from your application.

It's really that simple.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.

Try the RTA difference today! Call us at 800-249-1612 or check out our solutions at www.rtautomation.com.

A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience, all the better. Thirty years later, our mission remains the same: to move your data where you need it, when you need it and how you need it.

## **Specifications**

Web Interface FFATURES

Web Interface FEATURES			
Max Web Interface Connections	1 (Gateway acting as Client) / Unlimited (Gateway acting as Server)		
Encodings	JSON, XML		
Proxy Support	HTTP, SOCKS5 for Client		
Maximum Number of Input Data Points	1000 JSON Fields or 1000 XML Tags		
Maximum Number of Output Data Points	1000 JSON Fields or 1000 XML Tags		
HTTP Services	Client: POST only; Server: GET and POST		
S7 Client FEATURES			
PLC Support	S7 300/400/1200/1500		
Maximum Number of PLCs Supported	5		
Maximum Number of Inputs per PLC	150		
Maximum Number of Outputs per PLC	150		
Array Support	Yes, for all data types		
Supported Data Types	8Bit Int, 16Bit Int, 32Bit Int, 32Bit Float, Bool and String		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
Manual			

#### 

ELECTRICAL / ENVIRONMENTAL		DIMENSIONS		
DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA		LEDs	
Maximum Baud Rate	115K baud		, ,	
Operating Temperature	-40 C to 85 C	5		000
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	3.25 0		a line
ENCLOSURE / HARDWARE				
Size	4.2" x 3.25" x 1"			Port 0
Weight	7 oz			
Enclosure Type	Anodized Aluminum			
Mounting	Din rail or panel mount	1.00	4.19	1.00
LEDs	Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side	Din Rail		-
GATEWAY FEATURES & FUNCTIONS				
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Panel Mount		
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	NOT EXACTLY	WHAT YOU WEI	RE LOOKING FOR?
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	Real Time Automation offers a full line of gateway products. If this is not the one you were looking for, give us a call at 1-800-249-1612. Or, check out a listing at <u>www.rtautomation.com/products</u> . We also offer custom gateways to help customers dealing with unique needs or proprietary protocols.		
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateways diagnostics page. They can also be delivered to a connected device.			
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.			
CATALOG #	DESCRIPTION			

460WISC-N34 Connect up to 5 Siemens S7 PLCs via a Web Interface

Allen-Bradley, ControlLogix, CompactLogix, PLC-5 are registered trademarks of Rockwell Automation, Inc.



**Real Time Automation, Inc.** 

solutions@rtautomation.com